

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

STATE OF OREGON  
(Please type or print)

DEC 3 1973

State Well No. 2N/22E-32

(Do not write above this line)

STATE ENGINEER  
SALEM, OREGON

Call 19

(1) OWNER:

Name Howard DAVISON  
Address Box 246 - Arlington

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Cable  Dug   
Driven  Jetted  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

(5) CASING INSTALLED:

Threaded  Welded   
8" Diam. from 0 ft. to 104 ft. Gage 250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated?  Yes  No.  
Type of perforator used  
Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No  
Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom? Trimore  
Yield: 304 gal./min. with 15 ft. drawdown after 4 hrs.  
" " " " " "  
" " " " " "  
Bailer test gal./min. with ft. drawdown after hrs.  
Artesian flow g.p.m.  
Temperature of water 50° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite & Cement  
Well sealed from land surface to ft.  
Diameter of well bore to bottom of seal 9 1/2 in.  
Diameter of well bore below seal 9 in.  
Number of sacks of cement used in well seal sacks  
Number of sacks of bentonite used in well seal 3 sacks  
Brand name of bentonite Quik Seal  
Number of pounds of bentonite per 100 gallons of water 50 lbs./100 gals.  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Gilliam Driller's well number 360  
Section 32 T. 2N R. 22E W.M.  
Bearing and distance from section or subdivision corner

South Half Section 32

(11) WATER LEVEL: Completed well.

Depth at which water was first found 104 ft.  
Static level 25 ft. below land surface. Date 10-5-73  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8  
Depth drilled 200 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil Sandy Lt Brown	0	14	
Basalt Gray Fractured	18	40	
Conglomerate Hard	40	54	
Basalt Decomposed	54	110	104
Basalt - Fractured Gray	110	180	
Conglomerate Hard	180	200	25

Work started 11-10 19 73 Completed 11-16 19 73  
Date well drilling machine moved off of well 11-16 19 73

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Don Johnson Date 11-17, 1973  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 231

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Swift Water Well Drilling Inc  
(Person, firm or corporation) (Type or print)

Address 421 SW 6th Ave

[Signed] Joe Mc Knight  
(Water Well Contractor)

Contractor's License No. 576 Date 11-29, 19 73