NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

GILL 20

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
MAY 5 1978
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 2S/22E-15ca

State Permit No.

(1) OWNER:
Name Lee Rettyjohn
Address 10 Ne ORE

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☐
" Diam. from ft. to ft. Gage
" Diam. from EXISTING ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☐ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☐ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a ~~pump~~ AIR test made? ☑ Yes ☐ No If yes, by whom? Drillr
Yield: 500 gal./min. with 300 ft. drawdown after 1 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 66° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County GILLIAM Driller's well number
NE ¼ SW ¼ Section 15 T. 2S R. 22E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 498 ft.
Static level 120 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 13 1/2
Depth drilled 305 ft. Depth of completed well 575 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BLACK BASALT	270	498	
BLACK W TALC	498	560	H2O
BLACK BASALT	560	575	

Work started 4-12 1978 Completed 4-22 1978
Date well drilling machine moved off of well 4-22 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Larry Burd (Drilling Machine Operator) Date 4-22, 1978
Drilling Machine Operator's License No. 933

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name LARRY BURD WELL DRILLING (Person, firm or corporation) (Type or print)
Address 5543 SW DOUGLAS DR PEND
[Signed] Larry Burd (Water Well Contractor)
Contractor's License No. 544 Date 5-3, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119