TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

## WATER WELL REPRIECEIVED STATE OF OREGON WWW. 0. 4075 State

STATE OF OREGON

.1	I	L8	1975
•	•	_~	

1	W,e11	No.	45/21E-10	
---	-------	-----	-----------	--

STATE ENGINEER, SALEM, OREGON 97310 (Piease type within 30 days from the date of well completion.	HOVE WHATED RESOURCES DEPT.	¥o
Page	SALEM, OREGON	
(1) OTHERD.	(10) LOCATION OF WELL:	
(1) OWNER:	1	
Name City of Candon 97833	County Lilliam Driller's well n	210
Address ( ondow, William 1102)	14 14 Section 10 T. 4 A	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner
New Well S		
If abandonment, describe material and procedure in Item 12.	(44) YHAMED I EVIEL Complete	11
	(11) WATER LEVEL: Completed v	rell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 33	
Rotary Driven Domestic Industrial Municipal	Static level 130 ft. below land	surface. Date 6-26-75
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per squa	re inch. Date
CASING INSTALLED: . Threaded   Welded	(12) WELL LOG: Diameter of well	9"
Diam from Q ft. to 40 ft. Gage 1250		
"Diam. from ft. to ft. Gage	Depth drilled 636 ft. Depth of comp	leted well 630 ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	
Allen Avenue and the William An William	and show thickness and mature of each stratu with at least one entry for each change of forms	
PERFORATIONS: Perforated?  Yes No.	position of Static Water Level and indicate pris	
be of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Topsoil	0 3
	Abarro.	3 7
perforations fromft. toft.	Basalx	7 23
perforations from ft. to ft.	Rock brown + yellow clayston	22 38
perforations from ft. to ft.	Basaly	38 61
(7) SCREENS: Well screen installed?  Yes  No	Perh dark france	61 63
Manufacturer's Name	Rock med black	63 75
Type	Rock light from them clair	. 75 89
Diam. Slot size Set from ft. to ft.	Basalt	89 132
Diam, Slot size Set from ft. to ft.	Rob habt brown + yellow clause	132 139 W.B.
	Bassel	139 181
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basalt hard gray	181 206
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	Rock black + blue classtone	206 229
	Basalt black	229 261
Yield: gal./min. with ft. drawdown after hrs.	Basalt, hard gray	261 309
	Basalt, black	309 323
air -	Basalt hard gray	323 347
Beiles-test 300 gal./min. with 480 ft. drawdown after 2 hrs.	Rock black + blue Classitone	347 377 W.B.
Artesian flow g.p.m.	Basaer hard grey	377 446
emperature of water Depth artesian flow encountered ft.	Work started 6-16 1975 Complete	ed 6-25 1975
CONSTRUCTION:	Date well drilling machine moved off of well	6.26 1075
( a salas W	Drilling Machine Operator's Certification	Cont
77 to 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	This well was constructed under my	·
Well sealed from land surface toft.	Materials used and information reported	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	- 1 - 21 - 25
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date, 19./
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	665
Number of sacks of bentonite used in well seal sacks	The state of the s	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this report is
of water lbs./100 gals.	true to the best of my knowledge and be	
Was a drive shoe used? ⊠Yes □ No Plugs Size: location ft.	Name TROY GRIFFIN	
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 400 HERMISTOM AVE	HERMISTON OR
Method of sealing strata off	[Signed] / ray Grif	f->
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Conf	Factor)
Gravel placed from ft. to ft.	Contractor's License No Date	6-26 , 19.75

## NOTICE TO WATER WELL CONTRACTOR the original and first copy of this report are to be filed with the

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

State	Well	No.	

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(De not write above this line)

State Permit	No.	

Facq	
(1) OWNER:	(10) LOCATION OF WELL:
Name Caty of Condon	County Juliam Driller's well number
Address Conflon, Oregon 97823	4 1/4 Section /O T. 4.8. R. 21 E. W.M.
(A) THE OR TOPY (1)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon Reconditioning	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 11.
Rotary 12. Driven Domestic Industrial Municipal 12.	Static level ft. below land surface. Date
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded D	(12) WELL LOG: Diameter of well below casing
" Diam. from tt. to ft. Gage	Depth drilled ft. Depth of completed well ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?	position of Static Water Level and indicate principal water-bearing strata.
ype of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	The black + blue Claystone 446 489
perforations from	Rock Med delack 535 587 W.B.
perforations from	Basalt 587 611
perforations from	RACK black + blue claystone 611 622 W.B.
(7) SCREENS: Well screen installed?   Yes  No	Basalt, gran 622 630
Manufacturer's Name	
Type	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?   Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
· / / / / / / / / / / / / / / / / / / /	
~	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
emperature of water Depth artesian flow encountered ft.	Work started 19 Completed 19
CONSTRUCTION:	Date well drilling machine moved off of well 19
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 465
Number of sacks of bentonite used in well seal sacks	Drining stacinie Operator's Intense No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used?  Yes No Piugs Size: location 1.	true to the best of my knowledge and belief.
Did any strata contain unusable water?   Yes   No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Name TROY GRIFFIN  (Person, firm or corporation) (Type or print)  Address 900 HER MISTON AVE, HER MISTON ORE.
Method of sealing strata off	
Was well gravel packed?  Yes  No Size of gravel:	[Signed](Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 6-76 , 19.73