

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED

WATER WELL REPORT

RECEIVED

FEB 12 1975

STATE OF OREGON

APR 30 1974

State Well No. 55/23E-36a

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date
of well completion.

STATE ENGINEER

(Please type or print)

STATE ENGINEER

State Permit No.

SALEM, OREGON

(Do not write above this line)

SALEM, OREGON

Gilliam

Bond # 1-714-943

GILL, J. S.

(1) OWNER:

Name PETER O. CAMPBELL
Address

(10) LOCATION OF WELL:

County Driller's well number
SE 1/4 NE 1/4 Section 36 T. 55 R. 23 E W.M.

Bearing and distance from section or subdivision corner
APPROX 1/4 MILE WEST OF E. QUARTER
CORNER OF SEC. 36, 55-23E, W.M.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven
Cable Jetted
Dug Bored
Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

2" Diam. from 0 ft. to 25 ft. Gage 0.33"
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? CORNELL

Yield: 170 gal./min. with 67 ft. drawdown after 6 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used CEMENT
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 13" approx. in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 10 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 97 ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
COARSE GRAVEL	0	16	
CLAY - YELLOW-GRAY	16	24	
CLAY - REDDISH	24	30	30
FRACTURED ROCK			
GRAYISH-RED	30	90	18
(Possibly a permian type OR ROCK)			
BOULDERS	90	97	18

Work started Oct 20 1973 Completed MAY 25 1974

Date well drilling machine moved off of well ~~DATE~~ 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Peter O. Campbell Date 2-15, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name (Person, firm or corporation) (Type or print)

Address

[Signed] (Water Well Contractor)

Contractor's License No. Date 19