

GILL...2.2

ROTARY AIR DRILLED

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

STATE ENGINEER, SALEM, OREGON, 97310

within 30 days from the date of well completion

STATE ENGINEER

GA408

RECEIVED FEB 17 1969

State Well No.

State Permit No.

15/22-10 aa

(1) OWNER:

Name RAY Heim bigner
Address Lane, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
[] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from 0 ft. to 28 ft. Gage .250
Diam. from ft. to ft. Gage
Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [] Yes [X] No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 136 ft. below land surface Date
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?
1: gal./min. with ft. drawdown after hrs.
APPROX 200 GAL WATER BLOWN OVER TOP OF CASING PER MIN.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Cement
Depth of seal 28 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? [] Yes [X] No Depth
Was a drive shoe used? [] Yes [X] No
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [X] Yes [] No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Gilliam Driller's well number 79
NE 1/4 NE 1/4 Section 10 T. 15 R. 22E W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10"

Depth drilled 443 ft. Depth of completed well 443 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Top Soil SANDY, GRAVEL-Cemented, GREY BASALT, LAVA Rock-Red, LAVA Rock-Black, BASALT Rock-Black, LAVA Rock-Black, and BASALT Rock-Black.

Note:
from 0' to 306' Ten inch hole
306' to 365' Six inch hole
365' to 443' 5 inch hole.

Well drilled with air rotary
APPROX 200 GAL WATER BLOWN OVER TOP OF CASING PER MIN.

Work started 9/20 1968 Completed 10/23 1968
Date well drilling machine moved off of well 10/23 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Frank A. Crowe Date Jan 6, 1969
(Drilling Machine Operator)

Drilling Machine Operator's License No. 280

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME EDMUNDO BOEHR'S WELL DRILLING
(Person, firm or corporation) (Type or print)

Address Box 414 OAKLAND ORE

[Signed] Edmund Boehrs
(Water Well Contractor)

Contractor's License No. 556 Date 1-9, 1969