WATER WELL REPORT

STATE OF OREGON

(Please type or print)

/ /	
State Well No. 18/22E - 19 Co	1
State Downit No.	

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print)
(Please type or print)
(Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:			
Name Joe Exbu	County Ciller's well no	umber		
Address STAR Rt	SW 14 Stuly Section 17 T. /S	R. 22K		W.M.
O/FX Oly	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):	30			
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found $i8$	10		ft.
Rotary Driven Domestic Industrial Municipal	Static level // ft. below land s	surface. Date	e 9-	20-8
☐ Bored ☐ Irrigation	Artesian pressure lbs. per squar	e inch. Dat	e	
75) CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well below casing 12.1			
"Diam. from ft. to ft. Gage	Depth drilled /95 ft. Depth of compl		175	ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	m and aquif	er per	netrated.
7) PERFORATIONS: Perforated? Yes 140.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report (cipal water-	each cl bearing	hange in g strata.
Type of perforator used	MATERIAL	From '	То	SWL
Size of perforations in. by in.	_Sol/	0	5	<u> </u>
perforations from ft. to ft.	gravel Boy 1		3	
perforations from	Roy Ve S Q 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	33 3	- 21	
perforations from	How Grow Branch	CC 11	、	
(7) SCREENS: Well screen installed? Yes 7	KED Bashle	160 11	20	
Manufacturer's Name	RED Boras BANNE	180 /	90-	HIL
Type Model No.	yellas Tisk		•	
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.			 -	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	REGEIVED			
Air Pay	007374000	 	- i	
a pump test made? Yes No If yes, by whom?	UCI A 7 1980			
Yield: 1000 gal./min. with 155 ft. drawdown after hrs.	WATER RESOURCES DEPT			
" " " " " " " " " " " " " " " " " " " "	SALEM, OREGON			
Poller test gal./min. with ft. drawdown after hrs.		 	\dashv	
sian flow g.p.m.	C 10 00			0.0
emperature of water 6 Depth artesian flow encountered ft.	Work started Complete	ed Sept	- 24	1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Sens	20	<u>. 1965</u>
Well seal-Material used Youtland Comat	Drilling Machine Operator's Certification:			
Well sealed from land surface to 38 ft.	This well was constructed under my Materials used and information reported	direct su above are	perv true	ision. to my
Diameter of well bore to bottom of seal in.	best knowledge and belief //			
Diameter of well bore below seal in.	[Signed] Date C-C, 19.0			
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 1345			
How was cement grout placed?		•		
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdi	iction and t	his re	port is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my kilowledge and bel	# () 1	V.	_
Did any strata contain unusable water? Yes 440	Name (Person, firm or corporation)	Дуре	or prin	<u></u> \$}
Type of water? depth of strata	Address X 1 1 1 1/1 1/16	c7 / KOC	40	بومر
Method of sealing strata off	Isigned Linkel Hor	/	-	I
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contr			
Gravel placed from	Contractor's License No. 731 Date 7	0-10	•••••	., 19.80