## NOTICE TO WATER WELL CONTRACTOR

STATE OF OREGON

STATE OF OREGON

(Please type or print)

GEOSTATE ON State Permit No.

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGOER within 30 days from the date of well completion.

(1) OWNER: Paurse	(11) WELL T	ESTS:	Drawdown is an lowered below :	mount water level static level by whom?	is KeR
Address Mt Vernon Oregon	Yield: 540 s	gal./min. with	130 ft. di	awdown after	hrs.
(2) LOCATION OF WELL:  County CANT Driller's well number  SW 4 FE 4 Section 22 T. 30 R. 29 EW.M.	Bailer test Artesian flow	gal./min. wi	g.p.m. Date	" rawdown after	hrs.
Bearing and distance from section or subdivision corner	(12) WELL L Depth drilled 24	OG: Dia		pelow casing	5 // ft.
SE NA	Formation: Describe show thickness of a stratum penetrated,	e by color, che quifers and th	aracter, size of ne kind and nat	material and structure of the materi	cture, and
(3) TYPE OF WORK (check):  W Well Deepening Reconditioning Abandon bandonment, describe material and procedure in Item 12.	Soit	MATERIAL SAM Cel	Nd Y Mented WN	FROM  O  20	50 34
(4) PROPOSED USE (check):    Domestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted   Dug   Bored	CLAY	BROW STRIKS Yel	CAIUM CARAY	24 48 22 105 170	105
(6) CASING INSTALLED: Threaded Welded In the State of the Gage In the Control of the Co	CLAY	STRIP GRA 1 Ye	S Medique Ve L LLOW	235	235
(7) PERFORATIONS: Perforated? Wes I No Type of perforator used M 1 L S  Size of perforations 3/4 in. by 4 in.					
perforations from 2.0 ft. to ft.  perforations from ft. to ft.					
(8) SCREENS: Well screen installed					
Diam. Slot size Set from ft. to ft.  Slot size Set from ft. to ft.	Work started 6 - Date well drilling m	35 194		8-8	1962
(9) CONSTRUCTION:  Well seal—Material used in seal  Depth of sealft. Was a packer used? SANG	(13) PUMP:  Manufacturer's Nan  Type:	me Mo	PUM	Pye	<b>4</b> ,
Diameter of well bore to bottom of seal	Water Well Control  This well was true to the best of	drilled und	ler my jurisd	iction and this	report is
Gravel placed fromft. toft.  Did any strata contain unusable water?	NAME #0 A	Lo W Person, firm or N + A	SUP corporation)	TILIN (Type of prin	à Co
Method of sealing strata off  (10) WATER LEVELS:	Drilling Machine	Operator's			
Static level 23 ft. below land surface Date 8-8-62  Artesian pressure lbs. per square inch Date	[Signed] 7	nse No.		tractor)	., 19.6.3