

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

NC WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON
within 30 days from the date
of well completion.

STATE OF OREGON

State Well No. 255/31E-280a

(Please type or print)

State Permit No. G-6264 #1

NOV 22 1974

(Do not write above this line)

G-8550

Bond # EX-342-997

STATE ENGINEER

(1) OWNER:

SALEM, OREGON

Name Jack C. + Marie Futrell
Address P.O. Box 524
Burns, Ore. 97720

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

(5) CASING INSTALLED:

Threaded Welded

16" Diam. from 0 ft. to 67 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? Rossberg + Sarrigat
Yield: 1320 gal./min. with 25 ft. drawdown after 10 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used natural clay
Well sealed from land surface to 29 ft.
Diameter of well bore to bottom of seal App. 16 in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Homersy Driller's well number #1
1/4 1/4 Section 28 T. 255 R. 31E W.M.

Bearing and distance from section or subdivision corner 10 ft. N and 20 ft. W from SE corner of NE 1/4 of the NE 1/4

(11) WATER LEVEL: Completed well.

Depth at which water was first found 23 ft.
Static level 19 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing App. 15"

Depth drilled 123 ft. Depth of completed well 92 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	3	
fine sand	3	23	23
blue clay	23	29	
sand + gravel	29	35	
blue clay	35	40	
medium gravel	40	72	
blue clay	72	76	
medium sand	76	102	
medium sand, gravel, sea shells	102	123	

Work started Aug. 15 1974 Completed 10-22 1974
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] _____ Date _____, 19____
(Drilling Machine Operator)

Drilling Machine Operator's License No. _____

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name _____ (Person, firm or corporation) _____ (Type or print)

Address _____

[Signed] Jack Futrell Landowner.

Contractor's License No. _____ Date _____, 19____

RIMROCK SS - BURNS
 SAND - GRAVEL - CONCRETE - DUMP TRUCKING - EXCAVATION
 PHONE 573-2655 or 573-2411

**LEROY JACKSON
 CONSTRUCTION & REDIMIX**

550 E. MONROE
 LEROY JACKSON, OWNER
 BURNS, OREGON 97220

SOLD TO Jack Futrell DATE Feb 25 1975
 ADDRESS _____ CHARGE CASH ON ACCOUNT

QUANTITY	DESCRIPTION	AMOUNT
2 1/2	Cement	90.00
15	miles Milage	22.50
1	yard cement	45.00
15	miles Milage	22.50
	TOTAL	180.00

Od. 2/25
RFJ

Received by _____ By _____
 0197

ROSSBERG & SON
 Kenneth Rossberg
 P. O. Box 782
 CRANE, OREGON 97732
 Phone 493-2479

CUSTOMER'S ORDER NO. _____ PHONE _____ DATE Feb. 28, 1975

NAME Jack Futrell
 ADDRESS P.O. Box 534
BURNS, OREGON

SOLD BY	CASH	C.O.D.	CHARGE	ON ACCT.	MDSE. RETD.	PAID OUT	PRICE	AMOUNT
QTY.	DESCRIPTION						PRICE	AMOUNT
	Labor for surface seal around 16" well							
	we dug approx 3 feet and found a 20 pole around the casing. I ran a tape down it for 47 feet so we took a 24 foot piece of pipe with a 4" shoe on the end of it to make sure that we had 4" of clearance and then we poured 3 3/4 yds of cement into it. The well has been properly sealed. Will Dailer license # 269							
RECEIVED BY	<u>Jack Futrell</u>						TOTAL	75.00

1947
 All claims for returned goods MUST be accompanied by this bill.
 Form 810-D Available from **ROSSBERG**, Townsend, Mass 01469
 Thank You