NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

WATER WELL REPORT CEIVED STATE OF OREGON (Please type or print) MAR 15 1976 State Well No.

255/33E-1	1
-----------	---

filed with the

255/33E-1

within 30 days from the date of well completion. (Please type	ove the AFER RESOURCES TO FINIT No.	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Kenneth Rossberg	County Harney Driller's well number	
Address P.O. Box 782	S.W. 14 N.E. 14 Section 1 T. 258 R. 33E W.M.	
Crane Oregon 97732	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner	
New Well- ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) TYAMED FEVER CO. 14 I II	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
	Depth at which water was first found 32 ft.	
Cable	Static level 22 ft. below land surface. Date 2/17	
Dug □ Bored □ Irrigation Test Well □ Other □	Artesian pressure Ibs. per square inch. Date	
CASING INSTALLED: Threaded Welded K	(12) WELL LOG: Diameter of well below casing 12	
12 " Diam. from 0 ft. to 88 ft. Gage 250	100	
" Diam. from ft. to ft. Gage		
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
PERFORATIONS: Perforated? Ves M No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
2 01204 doi: 10 1200 10 1100		
Type of perforator used	MATERIAL From To SWL	
Size of perforations in. by in.	Topsoil 0 2 0	
perforations from ft. to ft.	Clay yellow 2 23 O	
perforations from ft. to ft.	Sandstone 33 26 0	
perforations fromft. toft.	Fine snad & pumice mixed 26 40 32	
(7) SCREENS: Well screen installed? To Yes 170 No	Black cinders & gravel 40 50 32	
(1) SCREENS: Well screen installed? Yes X No Manufacturer's Name	Gravel and clay 50 63 32	
Type Model No.	Fine sand brown 63 88 32	
Diam. Slot size Set from ft. to ft.	Clay blue 73 84 32	
Diam. Slot size Set from ft. to ft.	Black cinders 84 140 22	
	Clay blue 140 155 22 Cinders red 155 170 22	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Cinders red 155 170 22 CUlay blue 170 190 22	
Was a pump test made? Z Yes ☐ No If yes, by whom? driller		
yield: 1600 gal./min. with 48 ft. drawdown after 5 hrs.		
reid. 2000 gail/inin. with 10 it. drawdown after 0 ins.		
" " " " "	6-	
" " "	a de la distribuição de la distr	
Bailer test gal./min. with ft. drawdown after hrs.	A	
Artesian flow g.p.m.		
sperature of water 95 Depth artesian flow encountered ft.	Work started 17 1976 Completed 3/7 1976	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/7 1976	
	Drilling Machine Operator's Certification:	
Well seal—Material usedcement	This well was constructed under my direct supervision.	
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief	
Diameter of well bore below seal in.	[Signed] Date 3/8 19.76	
Number of sacks of cement used in well seal 15 sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 269	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? 🛭 Yes 🗌 No Plugs Size: location ft.	Name Roashers and Son	
Did any strata contain unusable water? 🗌 Yes 🔀 No	Name Rossberg and Son (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address Crane Oregon	
Wethod of souling strate off		
Was well gravel packed? ☐ Yes ☑ No Size of gravel: [Signed] ☐ (Water Well Contractor)		
	Contractor's License No. 272 Date 3/8/ 1976	
Gravel placed from ft. to ft.	Contractor's License No. 21.22 Date	