

NOTICE TO WATER WELL CONTRACTOR

RECEIVED
MAY 23 1966

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM 10, OREGON
within 30 days from the date of well completion.

STATE ENGINEER STATE OF OREGON
(Please type or print)

State Well No. 26/1384-12B1

State Permit No. G-2774

(1) OWNER:

Name Buffall Butte Ranch
Address Princeton, Oreg

(2) LOCATION OF WELL:

County Harney Driller's well number
N 1/2 of N 1/2 of Section 12 T. 24S. R. 33E W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED:

Threaded Welded
12" Diam. from 0 ft. to 177 ft. Gage .250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(7) PERFORATIONS:

Perforated? Yes No

Type of perforator used

Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(8) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Bentinite
Depth of seal 30 ft. Was a packer used? no
Diameter of well bore to bottom of seal approx 16 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Was well gravel packed? Yes No Size of gravel:
Gravel placed from " ft. to " ft.
Did any strata contain unusable water? Yes No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 24 ft. below land surface Date 9/25/63
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? driller
Yield: 1253 gal./min. with 26 ft. drawdown after 30 hrs.

" " " "
" " " "
" " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water cold Was a chemical analysis made? Yes No

(12) WELL LOG:

Diameter of well below casing 12"
Depth drilled 244 ft. Depth of completed well 240 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
TOP SOIL	0'	4'
HARD PAN	4'	17'
FINE SAND	17'	28'
BREEK CLAY	28'	92'
CLAY & SAND MIXED	92'	160'
CLAY & SANDSTONE	160'	181'
CINDER ROCK	181'	196'
PUMIE ROCK	196'	243'
LOOSE PUMIE GRAVEL	243'	244'

Copy
Work started 9/20 1963 Completed 9/25 1963
Date well drilling machine moved off of well 9/29 1963

(13) PUMP:

Manufacturer's Name 9
Type: " H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John W ROSSBERG
(Person, firm or corporation) (Type or print)
Address Box 443 BURNS, OREG.

Drilling Machine Operator's License No. 269
[Signed] John W. Rossberg
(Water Well Contractor)
Contractor's License No. 272 Date 9/29 1963