### RECEIVED

#### WATER WELL REPORT

NOV 5 1984

2/25/34E-611

STATE OF OREGON

WATER RESOURCES DEPT. SALEM. OREGON

State Well No	005/37C OXX
State Permit No.	

1) OWNER:	(10) LOCATION OF WELL:			
Name Alonzo B. (Lonnie) Leavell	County Harney Driller's well number #84-10			
Address 1705 N. Cole Road	SE % SE % Section 6 T. 26S R. 34E	W.M.		
Sty Boise, ID 83704 State		ivision		
2) TYPE OF WORK (check):	Address at well location: Crane, Oregon			
· · · · · · · · · · · · · · · · · · ·				
New Well	(11) WATER LEVEL: Completed well.			
	Depth at which water was first found	9/6/84		
3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 30 ft. below land surface.	Date		
Rotary Air Driven Domestic Industrial Municipal	Artesian pressure lbs. per square incl			
Rotary Mud	(12) WELL LOG: Diameter of well below casing	1.54		
S CASING INSTALLED: Steel  Plastic	Depth drilled 199 ft. Depth of completed w	ell It.		
Threaded $\square$ Welded $\square$	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry			
16"." Diam. from .+18" ft. to48 ft. Gauge	for each change of formation. Report each change in position of S	tatic Water Level		
1.6tt." Diam. from144 ft. to 15.2½ ft. Gauge	and indicate principal water-bearing strata.			
LINER INSTALLED:	MATERIAL From	To SWL		
	Lava Ash 0	10		
(6) PERFORATIONS: Perforated?   Yes   No	Lava Ash & Brown Sand 10	15		
Type of perforator used	Gry. Brnish. Clayw/Brn. Sand (Hd) 15	28		
Size of perforations in. by in.	Brown Sand W/Some Clay 20	30		
perforations from	Drown Band a re-	35		
perforations from	Coarse of real state realization			
perforations from ft. to ft.	coarse to fine sand & pea Gr.	40		
	& Sm.Amt.Clay(Brn.) 35 Coarse to Fine Sand & Pea Gr. 40	43		
(7) SCREENS: Well screen installed? ★AYes □ No  Manufacturer's Name ROSCOE MOSS  Type Shutter Screen Model No.	Coarse to Fine Sand & Pea			
Shutter Screen Model No.	Gravel (about 1/3 gry.clay) 43	45		
Type Model No.  Diam. 16" Slot Size 1/8 Set from 48 ft. to 144 ft.	Gray Clay 45	48		
Diam. Slot Size Set from ft. to ft.	Crse to fine Sand w/Some Pea			
Drawdown is amount water level is lowered	Gravel 48	50		
(8) WELL TESTS: below static level	Some clay at start-Crse. to			
Was a pump test made? ☑ Yes □ No If yes, by whom?	fine sandw/sma, gravel 50	55		
d: gal./min. with ft. drawdown after hrs.	Pumice Pieces & Crse. & Fine 55	65		
	Sand			
Air test gal./min. with drill stem at ft. hrs.	Brn. Siltstone w/Sand & Pumice 65	81		
Bailer test gal./min. with ft. drawdown after hrs.	Gray Lava - Fairly Soft 81	87 95		
Artesian flow g.p.m.  Depth artesian flow encountered ft.	Saile (Fine to Course)			
	Work State Co. 17-17	19 84		
(9) CONSTRUCTION: Special standards: Yes \( \text{NoX} \)  Well real_Material used   Concrete		10 04		
10 Book	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision	n Matarials used		
Well sealed from land surface to 18 Feet ft.  Diameter of well bore to bottom of seal 28 in.	and information reported above are true to my best know	ledge and belief.		
	[Signed] 6 Mark (northern Date	9/24/ <sub>19.84</sub>		
Diameter of well bore below seal28	(Drilling Machine Operator) Contracto	r's		
Number of sacks of cement used in well seal sacks  How was cement grout placed? Tremie Pipe	Drilling Machine Crerator's License No.			
now was cement grout placeu:	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this	report is true to		
Was pump installed?	the best of my knowledge and belief.  PETE COPE DRILLING CO., INC.			
Was a drive shoe used? ☐ Yes 🎽 No Plugs Size: location ft.	(Person, firm or corporation)	(Type or print)		
Did any strata contain unusable water? ☐ Yes ☐XNo	Address 6505 W. Chinden Blvd. Meridi	an, ID 8364		
Type of Water? depth of strata	[Gimed] Frank / hastring			
Method of sealing strata off 3/8 Min	[Signed] 1.342 Water Well Contractor)	0 /.		
Was well gravel packed? ½ Yes □ No Size of gravel: 3/8 Minu	Contractor's License No	, 1984.		
Gravel placed from 18' ft. to 155				

(Page 2)

#### WATER WELL REPORT STATE OF OREGON

## RECEIVED

# NOV 51984 NATER RESOURCES DEPT.

State Well No.	265/34E-6dk
----------------	-------------

SALEM.	DREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Alongo R (Tonnie) Leavell	County Driller's well number	
1705 H. Colo Dood	14 14 Section T. R.	W.M.
	Tax Lot # Lot Blk Subdivision	on
City Boise, Idaho State	Address at well location:	
(2) TYPE OF WORK (check):		
New Well □ Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.	
If abandonment, describe material and procedure in Item 12.		£ı.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found  Static level ft. below land surface. Date	ft.
Rotary Mud  Dug  Irrigation  Test Well  Other		
Cable   Bored   Thermal: Withdrawal   Reinjection	(12) WELL LOG: Diameter of well below casing	
CASING INSTALLED: Steel   Plastic	Depth drilled ft. Depth of completed well	ft.
Threaded □ Welded □ft. to	Formation: Describe color, texture, grain size and structure of materia thickness and nature of each stratum and aquifer penetrated, with at le for each change of formation. Report each change in position of Static and indicate principal water-bearing strata.	ast one entry
		CUIT
LINER INSTALLED:	MATERIAL From To	SWL
"Diam. from	Brn. Siltstone from fine to 3/4" mixed w/ Black Lava	
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No	Pieces to 3/4" 95 105	
Type of perforator used	Brn. Siltstone from fine to	
Size of perforations in. by in.	3/4" 105 115	
perforations from	Brn Sandstone & Siltstone Mix. 115 155	
perforations from		
perforations fromft. toft.		
(7) SCREENS: Well screen installed? ☐ Yes ☐ No		
Manufacturer's Name		
Type Model No		
Diam. Slot Size Set from ft. to ft.		
Diam.         Slot Size		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made?   Yes  No If yes, by whom?		
d: gal/min. with ft. drawdown after hrs.		<del> </del>
Air test gal./min. with drill stem at ft. hrs.		<del></del>
Bailer test gal./min. with ft. drawdown after hrs.		<u> </u>
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 19 Completed	19 19
(9) CONSTRUCTION: Special standards: Yes \( \text{No} \) \( \text{No} \)	Date well drilling machine moved off of well	
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision. M and information reported above are true to my best knowledg	aterials use e and belief.
Diameter of well bore to bottom of sealin.	and information reported above are true willy best knowledge	19
Diameter of well bore below seal in.	[Signed] Date Date	,
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	
How was cement grout placed?	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this rep	ort is true t
	the best of my knowledge and belief.	
Was pump installed?	Name	no overviet
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	(Person, firm or corporation)	be or henry
Did any strata contain unusable water?	Address	•••••
Type of Water? depth of strata	[Signed] (Water Well Contractor)	
Mathed of cooling strate off	( water well Contractor)	

Size of gravel: .....

Was well gravel packed? 🗆 Yes 🗆 No