The original and first copy of this report are to be filed with the	L REPORT		
		275/33E-1d	
SALEM, OREGON 97310 (Please type within 30 days from the date	- · · · · · · · · · · · · · · · · · · ·	(n	
of well completion.	pove this line)	. 1 0	
(1) OWNER: WATER RESOURCES DEPT	(10) LOCATION OF WELL:	Just Jok	
(1) OWNER: SALEM, OREGON Name RAID KILL NAME	1 11	Carlow May	
Address P.O. BOX 25 POINCETON, On 97721	County HAYN Driller's well no 1275		
101 101 101			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner  900 FT N. S. Line 80 FT W KE		
New Well Deepening   Reconditioning   Abandon	LINE		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 19 ft.		
Rotary	Static level 19 ft. below land surface. Date 16 June 7		
Dug   Bored   Irrigation Test Well   Other	Artesian pressure lbs. per squar	-	
(5) CASING INSTALLED: Threaded   Welded	(40)	10//	
2 " Diam. from 6 ft. to 8 ft. Gage	(12) WELL LOG: Diameter of well below casing		
" Diam. fromft. toft. Gage	Depth drilled // ft. Depth of completed well // ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and structure of materials;	
(S) DEDEOD ATIONS.	with at least one entry for each change of forma	tion. Report each change in	
(6) PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Brown Clay	0 18 1	
perforations fromft. toft.	Blue Clay!	18 67 19	
perforations fromft. toft.	Eine En act of Clare	109 110 19	
perforations from ft. to ft.	Shad Stone	11/2 125 19	
(7) SCREENS: Well screen installed?   Yes No	Sand Black Clay	125 145 19	
Manufacturer's Name	Black SAND - SMALL ON DUE	145 160 19	
Type Model No	160 BOCK	160 1/2 19	
Diam. Slot size Set from ft. to ft.	Rossel - Sand	162 166 19	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? X Yes □ No If yes, by whom? DoM AN			
- 131		77	
d: / 3 63 gal./min. with 30 ft. drawdown after 2 hrs.			
" " " "		•	
	The second secon		
211 0211/1017/2012	<u> </u>		
tesian flow g.p.m.			
nperature of water Depth artesian flow encountered ft.	Work started /5 June 19 78 Complete	ed / July 1928	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	15 July 1928	
Well seal—Material used C/A Y	Drilling Machine Operator's Certification:	<i>-</i>	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision.	
Diameter of well bore to bottom of seal in.	best knowledge, and belief. h/		
Diameter of well bore below seal in.	[Signed] Rayah Muluma or (Drilling Machine Operator)	Date 15 July 19 18	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No	0020	
How was cement grout placed?	Drilling Machine Operator's License No		
The second secon	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi		
Was a drive shoe used? X Yes □ No Plugs Size: location ft.	true to the best of my knowledge and beli	ef.	
Did any strata contain unusable water?   Yes No	Name (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address		
Method of sealing strata off			
Was well gravel packed?   Yes No Size of gravel:	[Signed] (Water Well Contr.	actor)	
Gravel placed fromft. toft.	Contractor's License No Date		
(USE ADDITIONAL SH		SP*45656-119	

NOTICE TO WATER WELL CONTRACTOR