NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT Application #

STATE OF OREGON

	_	$\iota \circ \iota$	- /		
State	Well No.	27:	5/34	E-96	d

	_	

	OREGON State Well No. 275/34E-95d			
within 30 days from the date	state Permit No			
(1) OWNER:	(10) LOCATION OF WELL:			
Name D. V. DOMAN				
Address Princton, Oregon	ST What I want to the state of			
Common and the common	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	O'N 1320'W From Center of			
New Well Deepening Reconditioning Abandon	Sec 9 1275, R34E			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 37			
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal				
Cable Detect Industrial Municipal Industrial Municipal Industrial	Jan			
CACING THOMATTERS	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 14			
14 " Diam from O ft to 60 ft Gage 250	Depth drilled 125 ft. Depth of completed well 125 ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;			
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer nenetrated			
PERFORATIONS: Perforated? Yes 4 No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used				
Size of perforations in. by in.	Ton Soil 02			
perforations fromft. toft.	Tan Soil 25			
perforations from ft. to ft.	Brown Class 5 20			
perforations from ft. to ft.	Blue Class. 20 50 25			
(7) SCREENS: Well screen installed? To you	Clay- grave mix 50 70 25			
(7) SCREENS: Well screen installed? Yes Manufacturer's Name	Colarge Sand 70 75 25			
Type Model No.	Clay- gravel mix 75 120 25			
Diam. Slot size Set from ft. to ft.	Course Sand 120 125 25			
Diam. Slot size Set from ft. to ft.				
(0) YURI I INDONG				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DEALINES			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	XEUEIVED .			
Yield: /200 gal./min. with 37 ft. drawdown after 5 hrs.	1 1 K 1 ma + / of 40 Km Cm :-			
" " " " " " " " " " " " " " " " " " "	JUN 1 1970			
H H H	VIATER RESOURCES DEPT			
Bailer test gal./min. with ft. drawdown after hrs.	CALEM, ONEGON			
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started March 15 19 79 Completed March 75 19 79			
*	1880700			
(9) CONSTRUCTION: Well seal—Material used				
	Drilling Machine Operator's Certification:			
Diometer of well in	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore below seal	best knowledge and belief.			
Number of sacks of cement used in well seal	[Signed] Date Date July 1979			
How was cement grout placed?	Drilling Machine Operator's License No. Land owner			
	<u>性</u> (1)			
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes Mo Plugs Size: location ft.	Name			
Did any strata contain unusable water? Yes 170	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address			
Method of sealing strata off	[Signed] WIV Homon			
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No Date			