

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

Please type or print

(Do not write above this line)

State Well No.

State Permit No.

285 / 272

285292-1122

app 2387

1530

(1) OWNER:

Name

Address

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Cable ☒ Aug ☐ Driven ☐ Jetted ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐ Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

16" Diam. from 0 ft. to 118 ft. Gage

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Type of perforator used

Size of perforations 3 in. by 1/4 in.

58" perforations from 113 ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Self

Field: 1130 gal./min. with ft. drawdown after 17 hrs.

" " " "

" " " "

Baller test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout

Well sealed from land surface to 21 ft.

Diameter of well bore to bottom of seal 22 in.

Diameter of well bore below seal 16 in.

Number of sacks of cement used in well seal sacks

How was cement grout placed?

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Harney Driller's well number

1/4 1/4 Section T. R. W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 22 ft.

Static level 10 ft. below land surface. Date 9-19-77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 16

Depth drilled 235 ft. Depth of completed well 235 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
0 - 22 Top Soil	0	22	
Blue Clay	22	74	
Coarse Sand & Gravel	74	76	
Hard Gray Clay	76	85	
Sand & Gravel	85	86	
Blue Clay	86	101	
Sand & Gravel	101	102	
Hard white Volcanic	102	103	
Blue Clay	103	149	
White Clay	149	176	
Blue Clay & Rock	176	203	
Fine Sand	203	235	

RECEIVED

AUG 30 1979

WATER RESOURCES DEPT.

SALEM, OREGON

Work started 9-19 1977 Completed 6-12 1979

Date well drilling machine moved off of well 6-12 1979

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date 19

(Drilling Machine Operator)

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name (Person, firm or corporation) (Type or print)

Address

[Signed] Henry Church (Water Well Contractor)

Contractor's License No. Date 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45856