STATE OF OREGON

WATER WELL REPORT (as required by ORS 537.765)

(for official use only)

WATER RESOURCES DEPT PLEASE TYPE or PRINT-IN

(1) OWNER:	(10) LOCATION OF WELL by legal descr	ription:
Name Ochoco National Forest	County Harney SW 1/4 NE 1/4 of Section	
Address P. O. Box 3623	Township 19S - Range 26	Ewm.
City Portland State OR	(Township is North or South) (Range is Ea	ast or West)
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address)	
	Delintment Lake Campground #1	
New Well Deepening Reconditioning Abandon Diffusion to the standard Reconditioning Abandon Diffusion 12.		
	(11) WATER LEVEL of COMPLETED W	TELL.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
Rotary Air 🖄 Driven 🗆 Domestic 🖾 Industrial 🗆 Municipal 🗆 Thermal:	Depth at which water was first found 81 ft. Static level 32 ft. below land surface. Date 10/10/84	
Rotary Mud Dug Irrigation Withdrawal Reinjection		
Other: Piezometric Grounding Test		
(5) CASING INSTALLED: Steel Plastic Welded Welded	12) WELL LOG: Diameter of well below casing	
Threaded \square Welded \square 8 "Diam from 2 ft to -18 ft Gauge .250		
Diam. from ft. to ft. Gauge	formation. Report each change in position of Static Water Level a	
	water-bearing strata.	
LINER INSTALLED: Steel	MATERIAL From	To SWL
6 Diam. from 2 ft. to -104 ft. Gauge 188	Overburden 0	12
	Brown coarse sandstone 12	81 32
(6) PERFORATIONS: Perforated? Yes No	broken brownlava WB 81	104
Size of perforations $\frac{1}{4}$ in. by $\frac{12}{2}$ in.	: <u></u>	
	. ====	
perforations from ft. to ft.		
perforations from ft. to ft.	_ <u>-</u> -	
(7) SCREENS: Well screen installed? Yes X No		
Manufacturer's Name		
TypeModel No	s Marri T - state b	
Diam Slot Size Set from ft. to ft.		-
Diam Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	1907	
Was a pump test made?		
d: gal./min. with ft. drawdown after hrs.		
,, n, n		-
Air test gal./min. with drill stem at ft. hrs.		
Bailer test 12 gal./min. with 6 ft. drawdown after 1 hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Date work started 10-8-84 /completed 10-	-10 - 84
(9) CONSTRUCTION: Special standards: Yes □ No ☒	Bate work started	
Well seal—Material used Cement		-10- ¹⁹ 84
Well sealed from land surface to -18 ft.	(unbonded) Water Well Constructor Certification (if	
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. information reported above are true to my best knowledge a	
Diameter of well bore below seal in.		
Amount of sealing materialsacks 💢 pounds 🗆	[Signed] Date	1/16 , 19 64
How was cement grout placed?DTESSURE GROUTED	s cement grout placed?	
hand nime	(number) (Surety Company Name)	
Was pump installed? Yes hand pump Depth 98 ft.	On behalf of <u>Crawford Well Drilling</u> , Inc. (type or print name of Water Well Constructor)	
Was a drive shoe used? Yes No Plugs		
Did any strata contain unusable water? Yes 🔼 No	This well was drilled under my jurisdiction and this report is true to the	
Type of Water? depth of strata	best of my knowledge and belief:	
Method of sealing strata off	(Signed) Say (Water Well Constructor)	
Was well gravel packed? Yes No Size of gravel:	(Water Well Constructor)	
Gravel placed from ft. to ft.	Control of the second s	