NOTICE TO WATER WELL CONTRACTOR - Contract The original and first copy of this report	D	,	
are to be filed with the	REPORT OF VED Well No.	30x 20E	-7770
SALEM, OREGON 97310 / 1 QQ (Please type			
within 30 days from the date of well completion.	MFR 24 M/M State Demait >	No	······································
(1) OWNED.	(10) LOCATION COE CARELL:		
(1) OWNER: Name Wallace L Coheman	1	_	٠- *
Name Wallace L Coheman Address Fields Ore	115		
Trends Offe			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner 2558' N 2722'W From SE Cor 5cc. 22		
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	· CAA.	ft.
Rotary Driven Domestic Industrial Municipal	Static level 60 ft. below land surface. Date 2-10-78		
Dug	Artesian pressure lbs. per square inch. Date		
(CASING INSTALLED: Threaded Welded	(40) 77777 7 0 0		
16 " Diam. from O ft. to 448 ft. Gage 1025	(12) WELL LOG: Diameter of well below casing O		
" Diam. from ft. to	Depth drilled 448 ft. Depth of completed well 448 ft.		
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL	From To	swL
Size of perforations $\frac{3}{32}$ in. by $\frac{2}{3}$ in.	TOP SOIL	0 18	
CH/FT perforations from 165 ft. to 448 ft.	Clay Gravel Boulders mixed	18 178	60
perforations from ft. to ft.	Gravel & Sand	178 188	
perforations from ft. to ft.	Brown Clay	188 208	
(7) SCREENS: Well screen installed? Yes No	Lavo Gravel & Sand	308 388	
Manufacturer's Name	Clay Gravel mixed	288 358	-
Type Model No	Land Grane	358 378	-
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Clay Chavel mixed	378 398	
Dien Sie Sie Sie Set Hom	Sand & Gravel	398 438	- 2-4
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay and Gravel mix.	438 448	
Was a pump test made? Yes □ No If yes, by whom? OWne			
Yield: gal./min. with ft. drawdown after hrs.			
" " " " " " " " " " " " " " " " " " " "	10 10 V		
" " " " " " " " " " " " " " " " " " "			·
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encounteredft.	Work started 2-3 1978 Complete	ed 2-27	1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2-10	1978
Well seal-Material used Concrete	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief		
Number of sacks of cement used in well seal	[Signed] Date 1, 19 (Drilling Machine Operator)		
How was cement grout placed? Concrete mix Truck	Drilling Machine Operator's License No.	*****	WERE STREET
and the second s	Water Well Contractor's Certification:		<i>y</i>
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address		
Method of sealing strata off	Walle of Polance		
Was well gravel packed? X Yes No Size of gravel: 74-4	[Signed] (Water Well Contractor)		
Gravel placed from ft. to448 ft.	Contractor's License No Date	7-19	., 19.28