NOTICE TO WATER WELL CONTRACTOR (3 | 1966

The original and first copy of this report are to be 1 ATE ENGINWATER WELL REPORT filed with the 1 ATE ENGINEER, SALEM, OREGON 97310 VI. OREGOISTATE OF OREGON

State Well No. 19/36-30 J

within 30 days from the date (Please typof well completion.	pe or print) 6 355 State Permit No
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name BILL POBERTSON	Was a pump test made? The Yes □ No If yes, by whom? DRILLER
Address DRe W.Sey OReGON	Yield: 744 gal./min. with/26 ft. drawdown after 4 hrs.
(2) LOCATION OF WELL:	
	Bailer test gal./min, with ft. drawdown after hrs.
County / ARNE Driller's well number	Artesian flow g.p.m. Date
NE 45 E 1/4 Section 30 T. 19.5 R. 36 E W.M.	Temperature of water 58 Was a chemical analysis made? Yes FNo
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled 238 ft. Depth of completed well 338 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Soil Medium 02
Well 🖻 Deepening 🗌 Reconditioning 🗍 Abandon 🖂	GRAVEL 28
In sandonment, describe material and procedure in Item 12.	CLAU BROWN 8 18
(4) PROPOSED USE (check): (5) TYPE OF WELL:	CLAN GREEN 18 103
Rotary C Driven C	CLAV BLUE 102/12
Domestic ☐ Industrial ☐ Municipal ☐ Cable ☐ Jetted ☐ Irrigation ☐ Test Well ☐ Other ☐ Cable ☐ Jetted ☐	CLAU GREEN 11223
Dug Dug Bored	ROOK BLACK 223 225
(6) CASING INSTALLED: Threaded Welded	CINDERS Red 275 228
ft. to ft. Gage	
(7) PERFORATIONS: Perforated? Yes Who	
Type of perforator used	
Size of perforations in, by in,	
perforations from ft. to ft.	
perforations from ft. to ft.	
ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? Yes 2-No	
Manufacturer's Name	
Model No. Slot size Set from ft. to ft.	
Diam, Slot size Set from ft. to ft.	Work started 3 - 5 1966 Completed 5 - 12 1966
	Date well drilling machine moved off of well 5 - 19 1966
(9) CONSTRUCTION:	(13) PUMP:
Well seal-Material used in seal BeNto Nitet Coment	Manufacturer's Name Pee Rless
Depth of seal 2 C ft. Was a packer used? SANA	Type: TURBINE HP. 60
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:
Were any loose strata cemented off? Yes Avo Depth	Water Wen Contractor's Certification.
Was a drive shoe used? ☑ Yes ☐ No	This well was drilled under my jurisdiction and this report is
Was well gravel packed? Tes PNo Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME HOLLOWAY DRILLING (6)
Did any strata contain unusable water? Yes No	Address (Person, rinn or corporation) (Type or print)
Type of water? depth of strata	Address
Method of sealing strata off	Drilling Machine Operator's License No.
(10) WATER LEVELS:	Issund Mall, ala Man In. In.
Static level 32 ft. below land surface Date 5-13-66	[Signed] (Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No