NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.





22/32/2-30P

Drawdown is amount water level is lowered below static level (11) WELL TESTS: (1) OWNER: Was a pump test made? ☐ Yes ☑ No If yes, by whom? Jack Mc Gee gal./min. with ft, drawdown after Harney, Oregon (2) LOCATION OF WELL: gal./min. with Bailer test ft. drawdown after hrs. Harney Driller's well number Artesian flow g.p.m. Date 30 T. 7.95 SR. 395 F.W.M. 1/4 Section Temperature of water Was a chemical analysis made? ☐ Yes ☐XNo Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing 12!! Depth drilled 202 ft. Depth of completed well 202 Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM (3) TYPE OF WORK (check): 90 coarse sand with water New Well Deepening 🔂 Reconditioning [Abandon [brown clay with coarse bandonment, describe material and procedure in Item 12. gravel - some water (5) TYPE OF WELL: PROPOSED USE (check): vellow clay-coarse gravel ☐ Driven ☐ Domestic 🗌 Industrial 🗎 Municipal 🗍 water bearing 120 126 Jetted Irrigation Strest Well Other ☐ Bored 126 vellow clay-trace of sand 1.75 yellow clay--trace of gravel 175 (6) CASING INSTALLED: Threaded | Welded X yellow clay--coarse gravel 12 "Diam from 43 ft. to 126 ft. Gage 250 196 water bearing -202 ______ Tolam, from ______ ft. to ______ ft. Gage ____ _____ Tiam. from _____ ft. to _____ ft. Gage ____ tested with compressor at 115 ft 97' drawdown - insufficient (7) PERFORATIONS: Perjorated? 😿 Yes 💻 No Type of perforator used · No further tests made Size of perforations in. by 60 12 20 14 perforations from 30 ft. to 126 ft. perforations from 43' of casing was in the well when perforations from I started drilling. First 43' was perforations from ft. to drilled by Mr. McGee. perforations from (8) SCREENS: Well screen installed Manufacturer's Name Set from 1962 Work started Nov. 141962 Completed Nov. 28 Slot sizeSet from Date well drilling machine moved off of well NOV. 1962 (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal Manufacturer's Name Depth of seal ft. Was a packer used? Diameter of well bore to bottom of sealin. Water Well Contractor's Certification: Were any loose strata cemented off? Tyes No Depth This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used?

Yes

No =: . Was well gravel packed? ☐ Yes ☒ No Size of gravel: Gravel placed from ft. to NAME Skinner & Sons (Person, firm or corporation) (Type or print) Did any strata contain unusable water? ☐ Yes 🔯 No Address P.O.Box 7 Crane, Oregon Type of water? Depth of strata Method of sealing strata off Drilling Machine Operator's License No. . (10) WATER LEVELS: Static level ft. below land surface Date Artesian pressure lbs. per square inch Date Contractor's License No. 372 Date Nov. 29, 1962