NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
AUG 30 1978
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 23s/27E-19d
State Permit No. G-8056

261 Harn

(1) OWNER:
Name Gene Clark
Address Riley Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
16" Diam. from 02 ft. to 20 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
d: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 0 ft. drawdown after 1 hrs.
esian flow g.p.m.
Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Portland Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 20 in.
Diameter of well bore below seal 18 in.
Number of sacks of cement used in well seal 21 sacks
How was cement grout placed? Mixed in Bucket and poured around pipe
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Harney Driller's well number
SE ¼ SW ¼ Section 19 T. 23S R. 27E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 150 ft.
Static level 65 ft. below land surface. Date Sept. 18-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 18"
Depth drilled 525 ft. Depth of completed well 525 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. **Report each change in position of Static Water Level and indicate principal water-bearing strata.**

MATERIAL	From	To	SWL
Top Soil	0	6	
Light Clay	6	10	
Gravel	10	12	
Brown Clay	12	42	
Sandstone	42	150	65
Sandstone Gravel Water Bearing	150	318	
Hard Red Clay	318	335	
(Sand Stone and Gravel water Bearing)	335	525	

Work started July 22 1977 Completed Sept. 18 1977
Date well drilling machine moved off of well Sept. 18 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Orval Buckner (Drilling Machine Operator) Date 8-15, 1978
Drilling Machine Operator's License No. 959

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Orval Buckner (Person, firm or corporation) (Type or print)
Address 1686 NE Neous Way Redmond Ore.
[Signed] Orval Buckner (Water Well Contractor)
Contractor's License No. 608 Date 8-15, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

Rt #2 Mr Buckner 9-24-78

SP*45656-119