·--- ·

₹Ξ

and the second s	a Entiur -			ra ji r			. -	
	A	LL REPO	ORT Harry	State We	ell No. 23	130-	-14 G	
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.	SALEM. ORDEON	FOREGON e or print)	293		rmit No			
(1) OWNER:		(11) W	ELL TESTS:	Drawdo	wn is amount v below static le	vater leve	l is	
Name Floyd H. Garland			Was a pump test made? Yes No If yes, by whom?					
Address Burns, Oregon			Yield: gal./min. with ft. drawdown after hrs.					
	· · · · · · · · · · · · · · · · · · ·	"	"		,,		,,	
(2) LOCATION OF WELL:	·	**			<u>,,</u>		"	
County Harney Driller's well number					20 _{ft. drawdo}	wn after	hrs.	
SW 14 SE 14 Section 14 T. 23S R. 30E W.M.			low ire of water	g.p.m.	pate nical analysis r	nadas FT V	Voc El No	
Bearing and distance from section or subdivision			ELL LOG:		· · · · · · · · · · · · · · · · · · ·		X	
		(12) 11			f well below ca	- ດ	-	
			Depth drilled 260 ft. Depth of completed well 260 ft.					
			: Describe by colo cness of aquifiers of enetrated, with at	r, character, and the kind least one en	size of materia and nature of try for each c	l and stru the mater hange of	cture, and ial in each formation.	
			MATE	RIAL	÷	FROM	то	
(3) TYPE OF WORK (check):		.,	Top Soil	T.		0	6.	
	tioning 🗌 Abandon 🗌		Hard Soil	_		6	10	
I andonment, describe material and procedu	re in Item 12.		Clay & Bo			10	60	
(4) PROPOSED USE (check):	(5) TYPE OF WELL:		Sand Stone			60 90	90	
Domestic 🐔 Industrial 🗆 Municipal 🗆	Rotary Driven		Volcanic R Pumice	JOCK		120	170	
Irrigation 🛘 Test Well 🗎 Other 🔻	Cable ∡ Jetted □ Dug □ Bored □		Cinders			170	195	
(6) CASING INSTALLED: Threaded Welded			Med Grave	el		195	230	
6 "Diam. from 0 ft. to 260 ft. Gage • 250			Red Cinde	rs -		230	240	
" Diam. from	*		Hard Rock			240	260	
	· ·						 	
(7) PERFORATIONS: Perfor	ated? KI Yes No							
Type of perforator used Toro	ch							
Size of perforations 3/8 in. by	4 in.						<u> </u>	
192 perforations from 240	ft. to260 ft.							
perforations from							-	
perforations from								
perforations fromft. toft. toft.								
(a) COREENC	· · · · · · · · · · · · · · · · · · ·							
• •	led? ☐ Yes ፟፟ ∏ No							
Manufacturer's Name		·			······································		 	
D. Slot size Set from		Work star	ted 10-6-65	1065	Completed 1C	 -15-6!	5 1965	
Diam, Slot size Set from	ft. to ft.		drilling machine				19	
(9) CONSTRUCTION:		(13) PI						
Well seal—Material used in sealBentonite			urer's Name	· · · *. · ·		*************		
Depth of seal20 ft. Was a packer used?YES		Type: H.P.						
Diameter of well bore to bottom of seal in. Were any loose strata cemented off? Yes No Depth		Water W	ell Contractor's	Certification	on:			
Was a drive shoe used? ☐ Yes ☒ No	-	This	well was drilled	l under my	jurisdiction	and this	report is	
	me of gravel:	true to t	he best of my k	nowledge a	nd belief.			
Gravel placed from ft. to ft.			Western I		Co.	pe or prin		
Did any strata contain unusuable water? 🏻 Yes 😾 No			(Person, firm or Burns, O		(T ₃	pe or prin	t)	
Type of water? depth of strata Method of sealing strata off					***************************************	9170	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Method of sealing strata off (10) WATER LEVELS:			Machine pera	tor's Licens	e No.	379		
Static level 150 ft. below land	surface Date, 10-15-6	[Signed]	Harl	Mater	Well Contractor)	}		
	are inch Date	Contract	or's License No.			-65	, 19.65	