NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731 within 30 days from the date of well completion.

WATER WELL REPORT TO ENGINEER
STATE OF OREGON
(Please type or print)

State Permit No.

State Permit No. ...

of well completion.			
(1) OWNER:	(11) WELL TESTS: Drawdown is amount v lowered below static lev	vater leve vel	l is
Name City of Hines	Was a pump test made? No If yes, by whom	. Drill	ler
Address Hines, Ore.	Yield: 675 gal./min. with 150 ft. drawdow	n after	8 hrs.
	" "		
(2) LOCATION OF WELL:	" "		
	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Harney Driller's well number SE 4 SW 4 Section 16 T 23S R 30E W.M.	Artesian flow g.p.m. Date		
74 611 /4 50012011 - 1	Temperature of water 64 Was a chemical analysis n	nade? 🔲 Y	es 🛛 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below case	sing 12	· ••
		9	45 ft.
	Depth drilled 345 ft. Depth of completed wel		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	he materi	il in each ormation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Top soil	0	
Well ⊠ Deepening □ Reconditioning □ Abandon □	Hard brown clay	4	$-\frac{1}{16}$
Sandonment, describe material and procedure in Item 12.	Brown clay and gravel	16	80
	Goarse gravel (cemented)	80	100
(4) PROPOSED USE (check): (5) TYPE OF WELL:	1 · · · · · · · · · · · · · · · · · · ·	100	120_
Domestic Industria Municipal Rotary Driven Cable Rotary Letted Rotary Driven Rotary Rotary	Hard red rock Brown clay	120	130
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	Pumice Pumice	130	165
(a) CACTAG TAGMATTED	Hard red rock	165	220
	Hard dark red volcanic rock	220	245
14 " Diam. from 0 ft. to 280 ft. Gage . 250	Hard red rock	245	255
ft. to	Pumice	255	269
ft. Gage ft. Gage	Red cinders	269	285
(7) PERFORATIONS: Perforated? ⊠ Yes □ No	Red cinders and rock (mixed)	285	300
Type of perforator used Torch	Multi colored cinders	300	327
Size of perforations 3/8 in. by 6 in.	Red cinders and hard red rock	327	345
160 perforations from 260 ft. to 280 ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			40
(8) SCREENS: Well screen installed? ☐ Yes ⊠ No			
Manufacturer's Name			
Model No.			
Diam Slot size Set from ft. to ft.	Work started April 12, 19 67 Completed Ap	ril 28	, 1967
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well April		1967
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Concrete	Manufacturer's Name		
Depth of sealft. Was a packer used?	Type: H.P.		
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:		
Were any loose strata cemented off? \square Yes \boxtimes No Depth			
Was a drive shoe used? ☐ Yes ☑ No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? ☐ Yes ☒ No Size of gravel:			
Gravel placed from ft. to ft.	NAME Western Drilling Co. (Person, firm or corporation) (Ty	ne or print	·)
Did any strata contain unusable water? ☐ Yes ☑ No	D O Boy 751 Burns Or	re or print egon	97720
Type of water? depth of strata	Address P.O. BOX 101 Dallis, 01		•••••
Method of sealing strata off	Drilling Machine Operator's License No. 379		
(10) WATER LEVELS:	[Signed]		
Static level 65 ft. below land surface Date 4-28-67	(Water Well Contractor)		0.5
Artesian pressure lbs. per square inch Date	Contractor's License No. 426 Date May 2	•	19 67