NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

WATER WELL REPARE CEIVED

	Well	No. 23	s /3	OF	3
•	****	210.	7	-	70

(Please type or print)

FEB181977 State Permit No.

of well completion. (Do not write ab	ove this HPR RESOURCES DEPT	
	(10) LOCATION OF WELL:	
(1) OWNER:		ımber <i>11</i>
Name Wendell E. Gronso		
Address 765 Pondenosa Village Bunas, One. 97720	SU 14 NE 14 Section 35 T. 23S	
	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):		
New Well Deepening		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	25 ft.
Rotary A Driven D Domestic A Industrial Municipal	Static level 20 ft. below land s	surface. Date 2-17-77
Cable	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded ☐ Welded 1	(12) WELL LOG: Diameter of well by Depth drilled 66 ft. Depth of complete Formation: Describe color, texture, grain size and the state of the state	eted well 64 ft.
ft. to ft. Gage	and show thickness and nature of each stratu	m and aquifer penetrated,
PERFORATIONS: Perforated? Tyes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each change in cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Top sail	0 2
perforations from ft. to ft.	Clay, brown	2 8
perforations from ft. to ft.	Sandstone, brown	8 20
perforations from ft. to ft.	Clay, nack, brown, broken	20 23
(7) SCPFFNS:	Lava rock, black	23 25 25 35
(7) SCREENS: Well screen installed? ☐ Yes 🔏 No Manufacturer's Name	*Sandstone, brown, fract.	25 35 35 64
Manufacturer's Name Type Model No	*Lava rock, black, fract.	64 66
Diam. Slot size Set from ft. to ft.	*Cindens, red	07 00
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? X Yes \(\square\) No If yes, by whom? driller		
Yield: 125 gal./min. with 18 ft. drawdown after 2 hrs.		
redu. 12) gardinir wier 10 16 drawdown drot 2 1225		
" " " "		
"		
Bailer test gal./min. with ft. drawdown after hrs.	-	
Artesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 2-75 19 77 Complet	ted 2-17 1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2 -1 8 1977
Well seal-Material used	Drilling Machine Operator's Certification	
Well sealed from land surface to	This well was constructed under my Materials used and information reported	airect supervision above are true to my
Diameter of well bore to bottom of seal10 in.	best knowledge and belief.	14
Diameter of well bore below seal	[Signed] District Avounces	Date 2-17 , 19.77
Number of sacks of cement used in well seal	(Prilling Machine Operator) Drilling Machine Operator's License No.	837
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	X.41
Brand name of bentonite	Water Well Contractor's Certification:	· ———
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and be	lief.
Was a drive shoe used? A Yes 🗆 No Plugs Size: location ft.	Name B& G Drilling	(Type or print)
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address P.O. Box 800 Hines,	Une,
Method of sealing strata off	[Signed Glosse] alamiet	265
Was well gravel packed? Yes X No Size of gravel:	(Water Well Con	ractor)
	Contractor's License No. 637 Date	2-17 19 Z