NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 235 - 3/2 -

State Permit No Legenung

(1) OWNER:	(10) LOCATION OF WELL:			
Name Charles Hoover	County Harney Driller's well number 1			
Address P.O. Box 974 Hines, Oregon 97739	NE 14 SE 14 Section 1 T. 23S R. 31E W.M.			
7//////	Bearing and distance from section or subdi	vision corner		
(2) TŸPĖ ÕF WORK (check):	_ <u></u>	. 4	t	
New Well ☐ Deepening ☑ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed	well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found			ft.
Rotary Driven Domestic Mindustrial Municipal Domestic Mindustrial Municipal	Static level 10 19th ft. below lan	nd surface. D	ate 1	<u> 2/12/</u>
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per so	juare inch. D	ate	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of we	ell below casir	ng8	in.
" Diam. from	Depth drilled 100 ft. Depth of completed well 265 ft.			
" Diam. fromft. toft. Gage" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;			
Diani, Ironi It. Gage	and show thickness and nature of each sta with at least one entry for each change of for			
(6) PERFORATIONS: Perforated? Yes XNo.	position of Static Water Level and indicate	principal wate	r-bearin	g strata.
Type of perforator used	MATERIAL	From	То	swL
Size of perforations in. by in.	Sandstone (brown)	165	210	10'9"
perforations from ft. to ft.	Pumice (white)	210	218	
perforations from ft. to ft.		218	265	<u>10'</u> 9
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? Yes No				
Manufacturer's Name				-
Type Model No.				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED			·
a pump test made? Yes W No If yes, by whom?	JAN 1 8 1981			
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT			
n n n	SALEM, OREGON			
n n n				
gal./min. with ft. drawdown after hrs.				
esian flow g,p,m.			./40	
Temperature of water Depth artesian flow encountered ft.	Work started 12/11 19 80 Com		2/12	19 80
(9) CONSTRUCTION:	Date well drilling machine moved off of we	en 12/13	3/	1980
Well seal—Material used	Drilling Machine Operator's Certificati			
Well sealed from land surface to	This well was constructed under Materials used and information repor	my direct	super re true	vision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.	4		
Diameter of well bore below seal in.	[Signed] (During Machine Operator)	Date	12/15,	<u>/, 1980</u>
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License N	Jo	1173	
How was cement grout placed?				 :
	Water Well Contractor's Certification:			•
	This well was drilled under my ju	isdiction and	d this r	eport is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and		1	
Did any strata contain unusable water? 🗌 Yes 🙀 No	Name Larry Root & Sous. (Person, firm or corporation)	(T y)	pe or prin	at)
Type of water? depth of strata	Address St.Rt. 2-14692 Hwy	20 Burns	, Ore	.97720
Method of sealing strata off	[Signed] Of the Market	Pont		
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well	· · · · · · · · · · · · · · · · · · ·	· · · ·	/
Gravel placed fromft. toft.	Contractor's License No781 Date	12/15/	80	, 19