

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print)

RECEIVED
235/3/E-1/22
OCT 12 1979
State Well No. 235/3/E-1/22
State Permit No. G-8968

Horn
328

(Do not write above this line)

WATER RESOURCES DEPT

(1) OWNER:

Name C.O. & Mary Salsbery
Address Rt. L, Box 74
Burns, Oregon 97720

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
 Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
12" Diam. from +1 ft. to 216 ft. Gage 250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Louvered
Size of perforations 3 in. by 1/8 in.
1152 perforations from 80 ft. to 104 ft.
2304 perforations from 114 ft. to 162 ft.
1152 perforations from 182 ft. to 206 ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Is a pump test made? Yes No If yes, by whom? W.W.W.
Yield: 360 gal./min. with 60 ft. drawdown after 8 hrs.
" " " " " "
" " " " " "
Pump test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

(9) CONSTRUCTION:

SEP 11 1979

Well seal—Material used cement grout
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 24 in.
Diameter of well bore below seal 24 in.
Number of sacks of cement used in well seal 60 sacks
How was cement grout placed? gravity flow

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: 3/8
Gravel placed from 18 ft. to 225 ft.

(10) LOCATION OF WELL:

County HARNEY Driller's well number
SE 1/4 SE 1/4 Section 1 T.23S. R.31E. W.M.

Bearing and distance from section or subdivision corner
480' North & 135' West of the SE corner of Sec 1

(11) WATER LEVEL: Completed well.

Depth at which water was first found 22 ft.
Static level 11 ft. below land surface. Date 9-6-79
Artesian pressure none lbs. per square inch. Date 9-6-79

(12) WELL LOG: Diameter of well below casing 24"

Depth drilled 225 ft. Depth of completed well 216 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	4	
Clay	4	22	
Gravel	22	26	
Gray clay	26	37	
Sand & gravel	37	54	
Clay	54	76	
Medium sand	76	85	
Clay	85	89	
Sand & gravel	89	100	
Tan clay	100	115	
Sand & gravel	115	117	
Pumice	117	162	
Clay stone	162	187	
Soft Sandstone	187	205	
Claystone	205	212	
Green claystone	212	225	

Work started 9-4 19 79 Completed 9-6 19 79
Date well drilling machine moved off of well 9-6 19 79

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James Bruce Date 9-6, 19 79
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1035

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Western Water Wells Inc.
(Person, firm or corporation) (Type or print)

Address P.O. Box 294, Burns, Oregon

[Signed] James Bruce (Water Well Contractor)

Contractor's License No. 659 Date 9-6, 19 79