NC

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
AUG 15 1966
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

Harney 3-78

State Well No. 23/31-6 E
State Permit No.

(1) OWNER:
Name Hobart Tiller
Address Burns, Oregon

(2) LOCATION OF WELL:
County Harney Driller's well number
SW ¼ NW ¼ Section 6 T. 23 S R. 31 E W.M.
Bearing and distance from section or subdivision corner
550' E of W Sec. (6) line, and
50' N of Center line

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☐ Welded ☒
12" Diam. from 0 ft. to 120 ft. Gage ¼"
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:
Perforated? ☒ Yes ☐ No
Type of perforator used
Size of perforations ½" in. by 2" in.
120 perforations from 55 ft. to 75 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal puddled clay
Depth of seal 18 ft. Was a packer used? no
Diameter of well bore to bottom of seal 15 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 13 ft. below land surface Date 7-3-66
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? driller
Yield: 200 gal./min. with 33 ft. drawdown after 3 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG:
Diameter of well below casing 0
Depth drilled 120 ft. Depth of completed well 120 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
topsoil-brown	0	6
clay-brown	6	8
clay-brown w/gravel & water	8	25
	25	80
gravel-fine	80	100
gravel-coarse	100	109
gravel-coarse w/clay-green	109	120

Work started 6-24 1966 Completed 7-3 1966
Date well drilling machine moved off of well 7-5 1966

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Skinner & Sons
(Person, firm or corporation) (Type or print)
Address Crane, Oregon
Drilling Machine Operator's License No. 277
[Signed] Mrs. Forrest Skinner
(Water Well Contractor)
Contractor's License No. 372 Date 7-19, 1966

(USE ADDITIONAL SHEETS IF NECESSARY)