STATE OF OREGON

WATER SUPPLY WELL REPORT (as required by ORS 537.765)

	A commercial and a
WELL I.D. # L 5	1740
START CARD #14	14601
WELL by legal descript	ion:
Latitude	Longitude

Instructions for completing this report are on the last page of this form.	31ARI CARD # 194(00)				
	(9) LOCATION OF WELL by legal description:				
Name Blackburn Family Trust	County Harney Latitude Longitude				
Address 707 Pondonsa Village City Burns State OR Zip 97720	Township 275 N or S Range 30 E E or W. WM.				
	Section 2 SE 1/4 NE 1/4				
(2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonment	Tax Lot 501 Lot Block Subdivision Street Address of Well (or nearest address) 33468 Scd Huse Lo				
	Street Address of V	Vell (or nearest addres	(s) 33708	700 LD	DA RE
(3) DRILL METHOD: ☐ Rotary Air ☐ Rotary Mud ☐ Cable ☐ Auger	(10) STATIC WAT	ER LEVEL:	-		
Other	30 ft. below land surface. Date 4-13-02				13-02
(4) PROPOSED USE:	Artesian pressurelb. per square inch Date				
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	(11) WATER BEARING ZONES:				
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	Donth at which water	una first found	50 '		
(5) BORE HOLE CONSTRUCTION: Special Construction approval ☐ Yes No Depth of Completed Well ☐ 15 ft.	Depth at which water was first found50 '				
Explosives used \square Yes \square No Type Amount	From To		Estimated Flow Rate		SWL
HOLE SEAL	50	175	15		30
Diameter From To Material From To Sacks or pounds					
10 0 20 Dentanua 0 20 15 Socks			-		
6 20 175					
	(12) WELL LOG:				
How was seal placed: Method $\square A$ $\square B$ $\square C$ $\square D$ $\square E$	Ground Elevation				
Mother poured dry & tamped				I as	O V
Backfill placed fromft.	Material		From	То	SWL
Gravel placed fromft. toft. Size of gravel	growel fill sand fine			13	
(6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Threaded	clay yell	7\ \ 1	13	50	
Casing: 6 +2 75 .250 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	grave clay		50	52	30
	tay yell		52	130	30
	claystone		130	134	30
	clay brn		1.34	150	30
Liner:	Claystone c		150		30
Drive Shoe used Inside Outside None	claystone	mird	172	175	30
Final location of shoc(s)		4, 4		[
(7) PERFORATIONS/SCREENS:			· ··		
Perforations Method	0-0-				
☐ Screens TypeMaterial Slot Tele/pipe	RECEIVED				
From To size Number Diameter size Casing Liner		2000			
	APR 2 4	2002			
	WATER RESOUR	ICES DEPT			
	SALEM, OF	EGON			
	L	3-02 Coi		12 63	
(8) WELL TESTS: Minimum testing time is 1 hour Flowing			npleted 4-	3-02	
Pump ☐ Bailer ☐ Air ☐ Artesian	(unbonded) Water Well Constructor Certification: 1 certify that the work I performed on the construction, alteration, or abandon-				
Yield gal/min Drawdown Drill stem at Time	ment of this well is in compliance with Oregon water supply well construction				
10 30 84 1 hr.	standards. Materials use knowledge and belief.	d and information rep	oorted above are tr	ue to the best	of my
				nber	
	Signed Date				
Temperature of water Depth Artesian Flow Found	(bonded) Water Well C				
Was a water analysis done? MO ☐ Yes By whom	I accept responsibility performed on this well d	ty for the construction uring the construction			
Did any strata contain water not suitable for intended use? Too little	performed during this tir	ne is in compliance v	vith Oregon water	supply well	
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	construction standards.	ins report is true to t	The best of my kno	mber	2 /
Depth of studio.	Signed Signed	thy K. P.	Jeley 1	Date %- /	7-01
ORIGINAL - WATER RESOURCES DEPARTMENT FIRST					