STATE OF OREGON WATER SUPPLY WELL REI (as required by ORS 537.765 & OA

PORT AR 690-205-0210)	06-29-2006	WELL LABEL # L 83213	
AR 090-203-0210)		START CARD # 185143	

(1) LAND OWNER Owner Well I.D.	(9) LOCATION OF WELL (legal description)							
First Name JOE Last Name WILLIAMS	12	w wm						
Company	Sec 7 SW 1/4 of the NW 1/4 Tax Lot 1300							
Address 70785 OLD EXPERIMENT STATION								
City BURNS State OR Zip 97720	Lat DMS or DD							
	Long Ombor DD DMS or DD							
(2) TYPE OF WORK New Well Deepening Conversion	Street address of well Nearest address							
Alteration (repair/recondition) Abandonment								
(3) DRILL METHOD	OLD EXPERIMENT RD							
Rotary Air Rotary Mud Cable Auger Cable Mud	(10) STATIC WATED I EVEL							
Reverse Rotary Other	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(f	t)						
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening							
Industrial/ Commercial Livestock Dewatering	Completed Well 06-27-2006 13							
Thermal Injection Other	Flowing Artesian? Dry Hole?							
	WATER BEARING ZONES Depth water was first found 22							
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy								
Depth of Completed Well 270.00 ft.	06-27-2006 22 257 1,000 13	_						
BORE HOLE SEAL sacks/		_						
Dia From To Material From To Amt lbs 29 0 20 Cement 0 20 18,000 P		\dashv						
24 20 173 Centent 5 25 16,600 T		\neg						
12 173 270	(11) WELL LOC	<u> </u>						
	(11) WELL LOG Ground Elevation							
How was seal placed: Method A B C D E	Material From To							
Other	topsoil silty loom 0 2							
Backfill placed from 173 ft. to 0 ft. Material 3/8 pea gravel	clay blk 2 7	_						
Filter pack from ft. to ft. Material Size	sand coarse 7 15 clay grey 15 40	\dashv						
Explosives used: Yes Type Amount	gravel sand clay 15 40 52	\dashv						
	clay brn 52 65	\dashv						
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	clay grey 65 75	\neg						
(a) (24 × 1 57 .250 (b) (x)	sand blk 75 85							
12 1.5 179 .250	clay grey 85 102							
	sand blk 102 115	_						
	clay grey 115 130 clay green 130 135	_						
	clay green 130 135 sand blk 135 172	\dashv						
Shoe Inside Outside Other Location of shoe(s)	pumice grey hard 172 240	\dashv						
	clay pumice gravel 240 245	\neg						
Temp casing Yes Dia From To (7) PERFORATIONS/SCREENS	pumice grey soft 245 257							
Perforations Method	clay green 257 270							
Screens Type wire wrap Material stainless steel		_						
Perf/ Casing/Screen Scrm/slot Slot # of Tele/ Screen Liner Dia From To width length slots pipe size	Date Started 06-05-2006 Completed 06-27-2006							
Screen Liner Dia From To width length slots pipe size Screen Liner 12 69 169 .1	(unbonded) Water Well Constructor Certification							
3, 10, 10	I certify that the work I performed on the construction, deepening, alterati	on, or						
	abandonment of this well is in compliance with Oregon water supply	well						
	construction standards. Materials used and information reported above are t	rue to						
	the best of my knowledge and belief.							
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date							
Pump	Electronically Filed							
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed							
100 2	(bonded) Water Well Constructor Certification							
	I accept responsibility for the construction, deepening, alteration, or aband-	onment						
	work performed on this well during the construction dates reported above. A							
Temperature 58 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well							
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.							
From To Description Amount Units	License Number 1424 Date 06-29-2006							
	Electronically Filed Signed TIMOTHY K RILEY (E-filed)							
	Contact Info (optional)							
	Contact into (optional)							

(5) B	ORE 1	НО	LE C	ONST	RUCTIO)N				(10) \$TAT	TC WATE	DIEWEI				
(5) BORE HOLE CONSTRUCTION BORE HOLE SEAL sacks/						(10) STATIC WATER LEVEL Water Bearing Zones										
Dia	Fron		To		Material	Fror		Γο An	nt lbs	Water B	earing Zones	3				
										SWL Date	From	To	Est Flow	SWL(psi)	+	SWL(ft)
				_												
								-							\sqcup	
				+											\vdash	
				$\dashv \vdash$											\vdash	
															H	
															H	
	FILT	ER	PACE	ζ											H	
	From		То	Materia	ıl Siz	ze									Ħ	
															Ħ	
<u></u>	A CINI	O /T	-							(11) WEL	L LOG					
(6) C	ASIN	G/L	INE	K							Material			From		To
Casi	ng Line	r	Dia	+	From To	o Gauge	Stl P	lstc Wl	d Thrd							
\vdash	+			\vdash			\mid	${f extcolored}$	1 H							
	+							\bowtie \vdash	1						_	
	+			\vdash				\bowtie \vdash	H						_	
\succ	\mathcal{H}							\bowtie \vdash	H							
\succ	\mathcal{A}			Ħ				\bowtie \vdash	+							
\sim	\mathcal{A}							\bowtie \vdash	1						-	
\sim							\sim	\forall	1							
\sim								\forall	1							
(7) P	ERFO	RA	TIO	NS/SC	REENS										_	
Perf/	Casing	/ Scr	een			Scrn/slot	Slot	# of	Tele/						_	
Screen		D		From	To	width	length	slots	pipe size	e						
]						
										∐						
										11						
										41 						
										11						
						-		+	1	+I $-$					\neg	
						+ +		+		11						
										1						
										11					_	
		_								' 					L	
(O) T		m E	ama	3.50			4.1									
(8) V	VELL	TE	515:	Minin	num testi	ng time is	s I hou	r								
Yiel	d gal/mi	n	Drav	vdown	Drill ste	em/Pump de	pth 1	Duration	(hr)		4 /TD					
										Commen	ts/Remarks					
w	ater Qı	nalit	v Co	ncerns	·					recording	the screen: we	don't know wi	nat number	we should be	e ent	ering for
				113	Dasamina	ion	Δm	ount U	Inits	slot length	and # of slots a	as it is continu	ious. The v	we should be vidth of scree	z ent en ic	100 and it
Fr	om	To) 		Descript	ЮП	Aille	June U	,11169		this number.				A1 15	.100 and it
<u> </u>													, j 5 u			