## **HARN 52004**

HARN 52004

STATE OF OREGON WATER SUPPLY WELL REPORT

(as required by ORS 537.765 & OAR 690-205-0210)

WELL LABEL # L 112486

START CARD# <u>/020970</u>

Instructions for completing this report are on the last page of this form.	
1) LAND OWNER Owner Well I.D.	(9) LOCATION OF WELL (legal description)
First Name Company  SALVAYSIDE  DAIRY  Last Name  DAIRY  LLC	County HARNEY Twp 26 N o(\$) Range 30 (For W W.M.
Address 4581 MAPLE GRUUU RD	Sec 13 Sw 1/4 of the NE 1/4 Tax Lot 4400
City SUNNY S'IDE State WA, Zip 98944	
	Tax Map Number
(2) TYPE OF WORK	Long OMS or DD
Alteration (repair/recondition)	
(2) DRILL METHOD	Street Address of Well (or nearest address) 300 42 WEAVER SPRING
(3) DRILL METHOD  ☐ Rotary Air	Byrns R
Reverse Rotary Other	(10) STATIC WATER LEVEL
Reverse Rotary Grief	Date   SWL(psi)   +   SWL (ft)
(4) PROPOSED USE  Domestic  Trigation  Community	Existing Well/Predeepening SWE(psi) SWE(tt)
☐ Industrial/Commercial ☐ Livestock ☐ Dewatering ☐ Injection	
Thermal Other	Completed Well   10-80-13   - 1/2   Flowing Artesian?
(#) PODE WOLF CONCEDUCTION OF THE TAX AND A TOTAL OF THE TAX AND A T	
(5) BORE HOLE CONSTRUCTION Special Standard: Yes (attach copy)	WATER BEARING ZONES Depth water was first found
Depth of Completed Well 36.5 ft.	SWL Date From To Est Flow SWL (psi) + SWL (fi)
BORE HOLE SEAL	10-30-13 112 312 400+ - 112
Dia From To Material From To Amount Scks/lbs	3
20 0 250 BENTONITE 0 30 37 SCK;	
12" 250 365	
	(11) WELL LOG Ground Elevation
How was seal placed: Method $\square$ , A $\square$ B $\square$ C $\square$ D $\square$ E	Material From To
POTHER POWED DRY/CEMENTING BASKET @30	SANOY SOIL O 3
Dother Pour ED DRY/CEMENTING BASKET @ 30' Backfill placed fromft. toft. Material	BLACK CINDERS 3 114
Filter pack from ft. to ft. Material Size	FRACTURED SANDSTONE - CLAY 114 255
Explosives used:  Yes Type Amount	SANDY GRAY CLAY   255   275
(C) C) C) C) C) D) FD	COARSE RED-BLK CINDER SAND 275 312
(6) CASING/LINER	GRAY CLAY 312 365
Csng Linr Dia + From To Gauge Steel Plastic Welded Thrd	RECEIVED BY OWRD
- 19" + 2 250 .250 - L	TEOLIVED BY OWND
	DEC <b>3 0</b> 2 <b>0</b> 13
Shoe I Inside Outside Other Location of shoc(s)	SALEM, OR
Temporary casing Yes Diameter From To	
<del></del> _	
(7) PERFORATIONS/SCREENS	Date Started
Perforations Method FACTORY	(unbanded) Water Well Constructor Cortification
Screens Type Material	(unbonded) Water Well Constructor Certification  1 certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with ORGO CALVEY BY OWRD
Screen slot Slot # of pipe	construction standards. Waterfals used and information reported above are true to
Perf Scrn Csng Linr Dia From To width length slots size	the best of my knowledge and belief.
V V 70 230 1/16 3 8514 PIPE	License Number DateNOV 1 2 2013
	License Number Date value
	- Signed
	Signed SALEM, OR
(8) WELL TESTS: Minimum testing time is 1 hour	(bonded) Water Well Constructor Certification
Pump ☐ Bailer ☐ Air ☐ Flowing Artesian	l accept responsibility for the construction, deepening, alteration, or
Yield gal/min   Drawdown   Drill stem/cump death   Duration (hr)	abandonment work performed on this well during the construction dates reported
400 118' 240 Y	above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge
	and belief.
Temperature 62 °F Lab analysis  Yes By	License Number 1355 Date 11-06 · 13  Signed 2. Jry
Nater quality concerns? Yes (describe below)	11/
From To Description Amount Units	Signed Chithun J. Jry
10 Description /Amount Omits	Contact Info. (optional)