STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) HARN 52469

WELL I.D. LABEL# L 1200 START CARD # 1028' ORIGINAL LOG #

		rage rorr
L	120012	
	1028723	

(as required by ORS 537.765 & OAR 690-205-0210)	2016 ORIGINAL LO)G #	
(1) LAND OWNER Owner Well I.D.			
First Name Last Name	(9) LOCATION OF WELL (le	gal description)	
Company SUNNYSIDE DAIRY LLC Address 4581 MAPLE GROVE RD		N/S Range 30.00 E E/W WM	
City SUNNYSIDE State WA Zip 98944	Sec <u>11</u> <u>SE</u> <u>1/4 of the NE</u>		
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number ' " or	Lot DMS or DD	
Alteration (complete 2a & 10) Abandonment(complete		DMS of DD DMS of DD	
(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd	Long or " or " or		
Casing:	30042 WEAVER SPRINGS RD. BURN		
Material From To Amt sacks/lbs			
Seal:	(10) STATIC WATER LEVEL		
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud		Date SWL(psi) + SWL(ft)	
Reverse Rotary Other	Existing Well / Pre-Alteration		
	Completed Well 1/14 Flowing Artesian	2016	
(4) PROPOSED USE Domestic X Irrigation Community Industrial/ Commercial Livestock Dewatering	-	epth water was first found 147.00	
Thermal Injection Other	SWL Date From To	Est Flow SWL(psi) + SWL(ft)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attach			
Depth of Completed Well 425.00 ft.	1/14/2016 147 425	1000	
BORE HOLE SEAL			
Dia From To Material From To Amt			
26 0 45 Bentonite Chips 0 45 95 20 45 293 Calculated 90.95			
12 293 425	(11) WELL LOG Ground El		
Calculated	Ground En		
How was seal placed: Method A B C D E Other POURED DRY	Material sandy soil	From To 0 2	
Backfill placed from ft. to ft. Material	black cinders	2 132	
Filter pack from ft. to ft. Material Size	broken grey clay with fine sand fractured cemented cinders	132 285 285 320	
Explosives used: Yes Type Amount	broken grey claystone	285 320 320 425	
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	g sy say say		
Proposed Amount Actual Amount			
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld			
Trom To Cauge bu Tiste Wil			
Shoe Inside Outside Other Location of shoe(s)			
Temp casing Yes Dia From To			
(7) PERFORATIONS/SCREENS			
Perforations Method			
Screens Type Material Perf/ Casing/Screen Scrn/slot Slot # of Te	Date Started 12/17/2015	Completed <u>1/14/2016</u>	
Screen Liner Dia From To width length slots pipe	(unbonded) Water Well Constructor		
		the construction, deepening, alteration, or upliance with Oregon water supply well	
	construction standards. Materials used	and information reported above are true to	
	the best of my knowledge and belief.	D .	
(O) WELL TERCTE M: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	License Number 1739	Date <u>1/31/2016</u>	
(8) WELL TESTS: Minimum testing time is 1 hour Pump Bailer Air Flowing Artesia	Signed CHARLES M FRY (E-filed)		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Cer		
1000 200 2	I accept responsibility for the construct	tion, deepening, alteration, or abandonment	
	work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well		
T. (0) OF Lebeschick V. Dec	construction standards. This report is true	npliance with Oregon water supply well to the best of my knowledge and belief.	
Temperature 68 °F Lab analysis Yes By Water quality concerns? Yes (describe below) TDS amount	License Number 1355	Date 1/31/2016	
From To Description Amount Unit			
	Signed ARTHUR L FRY (E-filed) Contact Info (optional)		
	Contact into (optional)		