STATE OF OREGON WATER SUPPLY WELL REPORT (as required by OPS 537.765 & OAR 690-205-0210)

HARN 52601

WELL I.D. LABEL# L 123039

START CARD # 1032168

ORIGINAL LOG #

Page 1 of 1

(as required by ORS 537.765 & OAR 690-205-0210)	10/19/2016	ORIGINAL LOG#	1032100	
1) LAND OWNER Owner Well I.D.				
1) LAND OWNER Owner Well I.D. First Name DAN Last Name KRYGER	(9) LOCA	ΓΙΟΝ OF WELL (legal	description)	
Company CRYSTAL CRANE HOT SPRINGS		EY Twp 24.00 S N	-	E/W WN
Address 59315 HWY 78		NE 1/4 of the SW		_,
City CRANE State OR Zip 97732 2) TYPE OF WORK New Well Deepening	Tax Map Num	her	Lot	
2) TYPE OF WORK New Well Deepening	Conversion Tax Map Num	ber" or 43.4406500	00 DMS	S or DD
Alteration (complete 2a & 10) Abandonm	ent(complete 5a) Long	" or <u>43.4406500</u> " or <u>-118.64150</u>	0000 DMS	S or DD
2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld T		treet address of well • N	earest address	, 01 22
Casing: Casing:	SAME AS AI			
Material From To Amt sacks/lbs		30.12		
Seal:				
3) DRILL METHOD		IC WATER LEVEL		
Rotary Air Rotary Mud X Cable Auger Cable	Mud	Dat	e SWL(psi) + SWL((ft)
Reverse Rotary Other	Existing V	Vell / Pre-Alteration		
	Completed		5 28	}
4) PROPOSED USE	·	Flowing Artesian?		
Industrial/ Commericial Livestock Dewatering	WATER BEAF	•	vater was first found 32.00	
Thermal Injection Other	SWL Date	From To Es	st Flow SWL(psi) + SWI	L(ft)
5) BORE HOLE CONSTRUCTION Special Standard	(Attach copy) 9/17/2016	31 55	14 2	22
Depth of Completed Well 192.00 ft.	9/21/2016	68 131		28
BORE HOLE SEAL	sacks/	00 131	-TO	
	o Amt lbs			
12 0 58 Cement 0 58				$\overline{}$
8 58 192 Calcular	ted 19.34			
Calcula	(11) WELL	LOG G 1F1 d		
		Ground Elevation		_
How was seal placed: Method A B C	DE top soil	Material	From To 0 1	
Other ft. to ft. Material			0 1	
Eiten and from ft. to ft. Material	Size clay green		13 25	
Filter pack from ft. to ft. Material	clay blue		25 31	
Explosives used: Yes Type Amount	clay grey		31 68	
5a) ABANDONMENT USING UNHYDRATED BENT	ONITE gravel & sand	with pumice	68 77	7
Proposed Amount Actual Amount	clay grey		77 113	3
6) CASING/LINER	clay green		113 12	
Casing Liner Dia + From To Gauge Stl 1	Plstc Wld Thrd clay red sticky		121 127	
8 X 2 82 .250 O	Cobbles & gra	vel black	127 133	
	clay red sandstone ligh	t brown	131 160 160 192	
		totown	100 172	
Shoe Inside Outside Other Location of shoe	``			
Temp casing Yes Dia From To)			
7) PERFORATIONS/SCREENS				
Perforations Method Holt Star Perforator				
Screens Type Material	Date Started	19/13/2016 Con	npleted <u>9/21/2016</u>	
Perf/ Casing/ Screen Scrn/slot Slot	# of Tele/			
Screen Liner Dia From To width length		Vater Well Constructor Certif		
Perf Casing 8 62 82 .375 1		the work I performed on the c of this well is in complian		
		tandards. Materials used and i		
		knowledge and belief.		
	License Numb	per [Date	
8) WELL TESTS: Minimum testing time is 1 hour				
·	Signed			
	ving Artesian (hardal) Was	W-II C	4:	
Yield gal/min Drawdown Drill stem/Pump depth Dura	_	er Well Constructor Certifica		,
40 130	T decept respo	nsibility for the construction, ed on this well during the constr		
		ring this time is in complian		
Tamanatura 140 °E Lab analysis Voc By		andards. This report is true to t		
Temperature 140 °F Lab analysis Yes By		Lisana Namban		
Water quality concerns? Yes (describe below) TDS amount From To Description Am	ount Units License Nume	1899 L	10/19/2016	
	Signed SAM	M P KINGREY (E-filed)		
		optional)		