RECERVED MAY 14 1962

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE ENGINEWATER WELL REPORT

State Well No. 23/32-29.5

| HRN State Permit No. ....

| (1) OWNER: J. J. Duhaine  | (11) WELL TESTS: Drawdown is amount water level is lowered below static level  Was a pump test made?   Yes Two If yes, by whom?   |
|---|---|
| Address   | Yield: gal./min. with ft. drawdown after hrs.   |
| Total Control   | <u> </u>  |
| (2) LOCATION OF WELL:   | Bailer test gal./min. with ft. drawdown after hrs.  |
| County HARNEY Owner's number, if any—  14 N W 14 Section 27 T. 2-35 R. 32 F W.M.                      | Artesian flow g.p.m. Date   |
| Bearing and distance from section or subdivision corner   | Temperature of water 20 Was a chemical analysis made?   Yes Z-No  |
|   | (12) WELL LOG: Diameter of well inches.   |
|   | Depth drilled 2/2 ft. Depth of completed well 83 ft.  |
|   | Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. |
|   | MATERIAL FROM TO  |
| (3) TYPE OF WORK (check):  New Well   | El Deur   |
| New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 11. | gray Clay 14 18   |
| PROPOSED USE (check): (5) TYPE OF WELL:   | Budies Stoud 18 70  |
| Domestic   Industrial   Municipal   Rotary   Driven   | John Clay 30 65   |
| Irrigation Test Well Other Dug Bored  | lilus Clary . 83 110  |
|   | blue sandy shale 110/40   |
| (6) CASING INSTALLED: Threaded Welded William from O ft. to Q O ft. Gage                              | hart blue sand 140 152  |
| "Diam. from ft. to ft. Gage   | - Went Clay 132 2/3   |
| ft. Gage ft. Gage   |   |
| (7) PERFORATIONS: Perforated?   | This well was plugger off   |
| SIZE of perforations // in. by / in.  | from 83 ft to 85 ft.  |
| perforations from 18 ft. to 20 ft.  | 1 1 1 1 1 1 1 1 1   |
| perforations fromft. toft.  | the senty purpose   |
| perforations from ft. to ft. perforations from ft. to ft.   | a ditte depth of 83 ft.   |
| perforations fromft. toft.  |   |
| (0) CODEENC. Well concentratelled. Fl. Vog. Fl. No.   | there 139 H. of assucrate   |
| (8) SCREENS: Well screen installed ☐ Yes ☐ No Manufacturer's Name                                     | hale.   |
| TypeModel No  |   |
| Slot size Set from ft. to ft.   |   |
| Dian  | Work started 4 - 29 19 62 Completed 5 - 4 1965  |
| (9) CONSTRUCTION:   | (13) PUMP:  |
| Was well gravel packed?  Yes No Size of gravel: Gravel placed from ft. to ft.                         | Manufacturer's Name   |
| Was a surface seal provided? ☐ Yes ☐ No To what depth?  | Type: H.P.  |
| Material used in seal—  | Well Driller's Statement:   |
| Did any strata contain unusable water?   Type of water?  Depth of strata                              | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.   |
| Method of sealing strata off  | Da al   |
| (10) WATER LEVELS:  | NAME (Person, irm, or corporation) (Type or print)  |
| Static level /5 ft. below land surface Date   | Address   |
| Artesian pressure lbs. per square inch Date 5-4   | Driller's well number   |
| Log Accepted by:  | [Signed]  |
|   | [Signed] (Weil Driller)   |
| [Signed] Date 19  | License No. 272 Date, 19  |