of this report are to be filed with the

WATER WELL REPORT GE VE D STATE OF OREGON AUG30 1972 State Well No. 2

STATE ENGINEER, SALEM, OREGON 97310 N S - 1972 (Please type or purity ATE ENGINEER of well completion. STATE ENGINEER SALEM OF STATE BY STATE OF OREGON 101/2 State Well No. 4 (Please type or purity ATE ENGINEER OF WITH A SALEM OF SALEM OF STATE BY TO AND TO AND THE SALEM OF SALEM O

SALEM. OREGON	
(1) OWNER:	(11) LOCATION OF WELL
Name Arla Allison	
Address 2430 East 31 St. Aurora; Colo.	SE % SE % Section 11 T. 23 R. 322 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
	8' west of E section line; 640' N of
New Well Deepening Reconditioning Abandon Life abandonment, describe material and procedure in Item 12.	S sec. line
Rotary Driven D	(12) WELL LOG: Diameter of well below casing 12"
Cable	Depth drilled 121 9 "ft. Depth of completed well 21 9"
The second of th	Formation: Describe color, texture, grain size and structure of materials.
(5) CASING INSTALLED: Threaded □ Welded ☑	and show thickness and nature of each stratum and aquifer penetrated,
12 " Diam. from 0 ft. to 37½ ft. Gage 1 11	with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
" Diam. fromft. toft. Gage	MATERIAL From To SWL
" Diam. fromft. toft. Gage	hrown soil 0 3
PERFORATIONS: Perforated?  Yes E No.	hard brown streak 3 3½
Type of perforator used	brown sandy soil-water 32 6 12
Size of perforations in. by in.	blue clay with occasional
perforations from ft. to ft.	streaks of sand 6 111
perforations from ft. to ft ft ft.	conglomeration of small
perforations fromft. toft.	rocks, gravel, sea shells
perforations from ft. to ft.	in blue clay with water 111 121 3'8"
perforations from ft. to ft.	
(F) COPERING	
(7) SCREENS: Well screen installed?   Yes I No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.	2.
	The same of the sa
(8) WATER LEVEL: Completed well.	
tic level 3'8" = ft. below land surface Date 5-17-72	
Artesian pressure lbs. per square inch Date	
(9) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? E Yes □ No If yes, by whom? driller  ld: 475 gal./min. with 27'1Ω'' drawdown after 7 hrs.	Work started F 70
,	Work started 5-10 1972 Completed 5-17 1972  Date well drilling mechine moved of a final start of the start of
" " " " " " " " " " " " " " " " " " " "	
" " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification:
Bailer test gal./min, with ft. drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief.
Temperature of water Was a chemical analysis made? [] Yes [KNo	[Signed] From State Minimum Date19
(10) CONSTRUCTION:	(Similar Machine Operator)
Well seal—Material usedConcrete	Drilling Machine Operator's License No. 10
Depth of seal 18 ft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of seal 15 in.	This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off?  Yes  No Depth	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No	NAME Skinner & Sons
Did any strata contain unusable water? 🔯 Yes 🗌 No	(Person, firm or corporation) (Type or print)
Type of watersurface depth of strata 31 to 61	Address Crane, Oregon 97732
Method of goaling streets are	lother the
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	The second section of the section of the second section of the section of the second section of the section of the second section of the sec
ALEVE PARCE IIV.	Contractor's License No. $372$ Date $6-5-$ , 19. $72$