NOTICE TO WATER WELL CONTRACTORS IN The original and first copyright of this report are to be 10 AUG 3 0 19 WATER WELL REPORT filed with the

state engineer, salem, oregon the date SALEM. OF CON (Do not write above this line)

| (1) OWNER: | (10) LOCATION OF WELL: |
|--|--|
| Name Norman AArtun | County Harney Driller's well number |
| Address 1460 S. Pearl Denver, Colo. | W1 ** NW 14 Section 3 T. 223 R. 321 - W.M. |
| | Bearing and distance from section or subdivision corner |
| (2) TYPE OF WORK (check): | 650' E of W sect line and |
| New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ | /3/0' S of N sec. line |
| If abandonment, describe material and procedure in Item 12. | (11) WATER LEVEL: Completed well. |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | Depth at which water was first found 17' |
| Rotary ☐ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐ | Static level 6 t ft. below land surface. Date 8-9-72 |
| Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐ | Artesian pressure lbs. per square inch. Date |
| CASING INSTALLED: Threaded Welded 12 " Diam. from 0 ft. to 38 ft. Gage 250 | (12) WELL LOG: Diameter of well below casing 12" |
| "Diam. fromft. toft. Gage | |
| PERFORATIONS: Perforated? Yes No. | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. |
| Type of perforator used | |
| Size of perforations in. by in. | |
| perforations from ft. to ft. | black clay water at 17: 0 103 6 brown clay with a little |
| perforations from ft. to ft. | |
| perforations from ft. to ft. | gravel 103 127 hard brown clay 127 174 |
| | gray sandstone 174 187 |
| (7) SCREENS: Well screen installed? ☐ Yes ☒ No | blue clay 187 216 |
| Manufacturer's Name | solid lt. grey punice |
| TypeModel No. | & water 216 236 8:71 |
| Diam. Slot size Set from ft. to ft. | |
| Diam. Slot size Set from ft. to ft. | |
| (8) WELL TESTS: Drawdown is amount water level is lowered below static level | |
| Was a pump test made XX Yes \(\subseteq No \) If yes, by whom? \(\dot{driv} \) \(\] er | 200 |
| Yield: 700 gal./min. with 45 ft. drawdown after 15 hrs. | The second secon |
| 11 11 11 11 11 11 11 11 11 11 11 11 11 | |
| " " | THE THE RESERVE THE STATE OF TH |
| Bailer test gal./min. with ft. drawdown after hrg. | |
| Artesian flow g.p.m. | |
| Temperature of water Depth artesian flow encounteredft. | Work started 8-8 1972 Completed 8-18 1972 |
| (3) CONSTRUCTION: | Work started 8-8 1972 Completed 8-18 1972 Date well drilling machine moved off of well 8-29 1972 |
| Well seal—Material usedpuddled clay | Drilling Machine Operator's Certification: |
| TYTATI COLUMN TO A STATE OF THE | This well was constructed under my direct supervision. |
| Diameter of well bore to bottom of seal 15 in. | This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. |
| Diameter of well bore below seal 12 in. | |
| Number of sacks of cement used in well seal sacks | [Signed] 7 Mult Munitr Date 8-29, 1972. |
| Number of sacks of bentonite used in well sealsacks | Drilling Machine Operator's License No. 10 |
| Brand name of bentonite | |
| Number of pounds of bentonite per 100 gallons | Water Well Contractor's Certification: |
| of waterlbs./100 gals. | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. |
| Was a drive shoe used? [5] Yes [] No Plugs Size: location ft. | Name Skinner & Sons |
| Did any strata contain unusable water? Yes No | (Person, firm or corporation) (Type or print) |
| Type of water? depth of strata | Address Crane Oregon |
| Method of sealing strata off | A |
| Was well gravel packed? ☐ Yes Æ No Size of gravel: | [Signed] |
| Gravel placed from ft. to ft. | Contractor's License No. 372 Date 8-29 19 72 |
| The state of the s | 19 12 |