NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

water resources department SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State	Well No. 235/32/2E -2
State	Permit No.
	APPL. G-10209

(1) OWNER:	(10) LOCATION OF WELL:
Name Dennis J. Benton	County Harney O Driller's well number
Address 1264 E. Santiam	FREE V WH / 1 CT - 27 - 27 - 70 TF
Stayton, Oregon 97383	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Middle of 160
New Well 🗷 Deepening 🗌 Reconditioning 🗎 Abandon 🗀	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 32
Cable Domestic Industrial Municipal	Static level 18 ft, below land surface. Date 7/6/79
Dug   Bored   Irrigation \( \text{D} \) Test Well   Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 12 Welded 12 Welded 12 Welded 13 Welded 14 Welded 15	(12) WELL LOG: Diameter of well below casing 12"
" Diam fromft. toft. Gage	Depth drilled 265 ft. Depth of completed well 265
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials
PERFORATIONS: Perforated?  Yes X No.	and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change i position of Static Water Level and indicate principal water-bearing strate
Type of perforator used	MATERIAL From To SWL
Size of perforations in, by in.	top soil and hardpan 0 18 SWL
perforations fromft. toft.	Blue clay 18 32
perforations from	sand & gravel 32 46
perforations from ft. to ft.	Brown clay 46 93
(7) SCREENS: Well screen installed?   Yes X No	gravel & pumice stone 93 114
Manufacturer's Name	Blue clay 114 198 gravel & pumice, & Black sand 198 220
Type Model No.	gravel & pumice, & Black sand 198 220 Blue clay 220 265
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	Well appears to have adequate amount of
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	water
Was a pump test made? Tyes X No If yes, by whom?	DEACUER
Yield: gal./min. with ft. drawdown after hrs.	- KEUEIVEU
n II	JUL 2 4 1979
<u>" " " " " " " " " " " " " " " " " " " </u>	
Bailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT.
Artesian flow g.p.m.	SALEM, OREGON
perature of water Depth artesian flow encountered ft.	Work started 6/27 19 79 Completed 7/6 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/7 1979
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal 20 in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] 7 1979
Sacks	(Drilling Machine Operator)
How was cement grout placed? pressure	Drilling Machine Operator's License No.
	Water Well Contractor's Certification:
	I Ills well was drilled under my jurisdiction and this report is
Was a drive shoe used? XYes I No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?   Yes   No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address
Method of sealing strata off	
Was well gravel packed? ☐ Yes ■ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No
	19 19