The original and first copy of this report are to be filed with the NOTICE TO WATER WELL CONTRACTOR VATER WELL REPORT TE OF OREGON WATER RESOURCES DEPARTME SALEM, OREGON 97310 JUN12 1978 (Please type or print) State Permit No. ... within 30 days from the date of well completion. WATER RESOURCES DEPT. SALEM, OREGON (10) LOCATION OF WELL: (1) OWNER: County HARNEY Driller's well number NE 14 MAN 14 Section 4 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): 1940 FT. EAST OF NW CORNER 50 FT, SOUTH OF NORTH LINE OF SEC. 4 Reconditioning [Abandon [] New Well Deepening [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven [Rotary Domestic | Industrial | Municipal | Static level ft. below land surface. Date Cable Jetted Irrigation Test Well Other Bored Artesian pressure lbs, per square inch. Date Disa CASING INSTALLED: Threaded | Welded | W (12) WELL LOG: Diameter of well below casing 123/4" Diam. from 6 ft. to 189 ft. Gage 250 ft. Depth of completed well Depth drilled / F 9 " Diam. from _____ft. Gage Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? Pyes No. Type of perforator used MILL MATERIAL SLOT SOIL Size of perforations SANDY 10 12 Rous AROWN 10 23 FINE GRAUEL 30 GRAUEL COARSE ORQ. ... perforations from . GRAY CLAY WITH (7) SCREENS: Well screen installed? | Yes | No SAND STREAKS 76 Manufacturer's Name PUMICE 120 Diam. Slot size _____ Set from ____ ft. to ____ PUMICE 120 Diam. Slot size Set from PUMICE WITH 126 Drawdown is amount water level is lowered below static level (8) WELL TESTS: WATER STRATAS Was a pump test made? A Yes I No If yes, by whom? Kasa BERG Yield: 454 gal./min. with 100 ft. drawdown after 6 hrs. gal./min. with ft. drawdown after Bailer test Artesian flow g.p.m. 1969 Completed perature of water Depth artesian flow encountered ft. 11-13 Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used CEMENT GROUT Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Diameter of well bore to bottom of seal 20" best knowledge and belief. W Date 5/22 , 1978 Diameter of well bore below seal 20 " in. [Signed] (Orilling Machine Operator) PRILLED BY
Drilling Machine Operator's License No. LAND OUNERS Number of sacks of cement used in well seal Water Well Contractor's Certification: B. TRUNNELL This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used Yes Yes Plugs Size: location DALE HEARRELL

Address

[Signed]

Contractor's License No.

Did any strata contain unusable water? 📋 Yes 📑 No

Was well gravel packed? ☐ Yes ☐ No Size of gravel:

Gravel placed from 26 ft. to 18 7 ft.//2 TON

Type of water?

Method of sealing strata off

(Person, firm or corporation)

(Water Well Contractor)

. Date