NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED
MAR 24 1975
STATE ENGINEER
SALEM, OREGON

RECEIVED
NOV 4 1974
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 23S/33E-6ad

State Permit No. Harn. 675

(1) OWNER:

Name Jack Davis

Address Buchanan Rt. Burns, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

10 " Diam. from plus 1 ft. to 79 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "

Bailer test 100 gal./min. with 10 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

[illegible]perature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used bentonite slurry

Well sealed from land surface to ~~18~~ 20 ft.

Diameter of well bore to bottom of seal 15 in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal 0 sacks

Number of sacks of bentonite used in well seal 150# ~~sacks~~

Brand name of bentonite bulk

Number of pounds of bentonite per 100 gallons of water 1000 lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Harmey Driller's well number

SE ¼ NE ¼ Section 6 T. 23S R. 33E W.M.

Bearing and distance from section or subdivision corner

100' Nof center sec. line & 176' W of E secl line

(11) WATER LEVEL: Completed well.

Depth at which water was first found 88 ft.

Static level 9 ft. below land surface. Date 9-29-74

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10"

Depth drilled 93 ft. Depth of completed well 93 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
brown topsoil	0	3	
hardpan	3	10	
sandy clay	10	15	
brown clay	15	40	
multi-color clay	40	88	
brown silt-water bearing	88	93	9

Work started 9-27 1974 Completed 9-29 1974

Date well drilling machine moved off of well 9-30 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Forrest Skinner Date 10-21, 1974.
(Drilling Machine Operator)

Drilling Machine Operator's License No. 10

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Skinner & Sons
(Person, firm or corporation) (Type or print)

Address Crane, Oregon 97732

[Signed] Catherine Skinner
(Water Well Contractor)

Contractor's License No. 372 Date 10-21- , 1974

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119