## MAY 15 1981

WATER WELL REPORT STATE OF OREGON

## WATER RESOURCES DEPT SALEM, OREGON

State Well No.	235	34	F-70b
	- 1		7
State Permit No.		<u>_</u>	8157-

(Harn) m	/ Wall #4			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Bill Gehrke	. **			
Address 2160 Sth. Adams	3.75.0	- 24 2		
City Denver State Colo.	T	R. 34 E. W.M.		
(2) TYPE OF WORK (check):	Address at well location: 6 mi. south on C	Subdivision		
	road, 600ft east of road	rane-Buchannan		
New Well   Deepening □ Reconditioning □ Abandon □		-		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	eli.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	16		
Rotary Air   Driven   Domestic   Industrial   Municipal   Rotary Mud   Dug   Irrigation   Test Well   Other   D		and surface. Date 5/14/8		
7 D 1 D 1	Too. pe	r square inch. Date		
The injection in the in	(12) WELL LOG: Diameter of well below of	casing 12		
(5) CASING INSTALLED: Steel Relatic	Depth drilled 230 ft. Depth of completed well 230 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry			
Threaded $\Box$ Welded $\mathbf{x}$				
"Diam from ft. to ft. Gauge	101 each change of formation. Report each change in n	osition of Static Water Level		
LINER INSTALLED: no	and indicate principal water-bearing strata.	v		
_	MATERIAL	From To SWL		
	soi1	0 10 0		
(6) PERFORATIONS: Perforated? ☐ Yes X No	10 brown clay	10 25 20		
Type of perforator used	rock, broken, grave1	25 70 50		
Size of perforations in. by in.	clay, hard blue	70 110 50		
perforations from	clay, grey hard	110 125 40		
perforations from ft. to ft.	rock, hard	125 135 20		
perforations from	claystone, green	135 150 18		
(7) SCREENS: Well screen installed?   Yes X No	claystone, blue, with gravel	150 225 16		
Manufacturer's Name	gravel, small to large, W.B.	225 230 10'4"		
Type Model No.				
Diam. Slot Size Set from ft. to ft.				
Diam. Slot Size Set from ft. to ft.				
(8) WELL TESTS. Drawdown is amount water level is lowered				
below static level				
a pump test made? ☐ Yes X No If yes, by whom?				
d: gal/min. with ft. drawdown after hrs.				
" " "				
Air test gal./min. with drill stem at ft. hrs.				
Bailer test 50 gal./min. with 2 ft. drawdown after 1 hrs.				
Arcsian flow g.p.m.				
perature of water 52 Depth artesian flow encountered ft.	Work started 4/19 19 81 Completed	5/1 1981		
(9) CONSTRUCTION: Special standards: Yes \( \text{No.} \) No.	Date well drilling machine moved off of well 5/1	1981		
Well seal—Material used cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my direct sup	permision Motorials used		
Diameter of well bore to bottom of seal	and information reported above are true to my bes	st knowledge and belief.		
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 5/14 1981		
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 1188			
How was cement grout placed? pumped				
	Water Well Contractor's Certification:			
Was pump installed?	This well was drilled under my jurisdiction a the best of my knowledge and belief.	and this report is true to		
Was a drive shoe used? ★ Yes □ No Plugs Size: location ft.	Name H.D. Woodruff Drilling			
Did any strata contain unusable water?  Yes No	(Person, firm or corporation)	(Type or print)		
Type of Water? depth of strata	Address Box 1943 Burns, Oregon 93	7.7.20		
Method of sealing strata off	[Signed] Harry Illoch	russ		
Was well gravel packed? ☐ Yes 🔀 No Size of gravel:	(Water Well Contractor)			
Gravel placed from	Contractor's License No717Date	C5/14,19.81		
NOTICE TO WATER WELL GOVERN CORD				