

23s | 34e - 19cd

State Permit No.

(Do not write above this line)

(10) LOCATION OF WELL:

County	Harney		Driller's well number	
SE	¼ SW	¼ Section 19	T. 23S	R. 34E
			W. M.	

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft.

Static level 18 ft. below land surface. Date June 20, 81

Artesian pressure lbs. per square inch. Date

(4) PROPOSED USE (check):

Rotary	☒	Driven	☐	Domestic	☐	Industrial	☐	Municipal	☐
Cable	☐	Jetted	☐	Irrigation	☒	Test Well	☐	Other	☐
Dug	☐	Bored	☐						

Threaded ☐ Welded ☒

16" Diam. from 0 ft. to 107 ft. Gage .250
 " Diam. from ft. to ft. Gage
 " Diam. from ft. to ft. Gage

Perforated? ☐ Yes ☒ No.

Type of perforator used			
Size of perforations	in. by	in.	
perforations from		ft. to	ft.
perforations from		ft. to	ft.
perforations from		ft. to	ft.

Well screen installed? ☒ Yes ☐ No

Manufacturer's Name **Johnson**
 Type **H1 - Cap**
 Diam. **1 1/2** Slot size **50** Set from **57** ft. to **97** ft.
 Diam. Slot size Set from ft. to
 Diam. Slot size Set from ft. to

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Agri-lines

yield: 250 gal./min. with 72 ft. drawdown after 3 hrs.

" " "

" " " "

Bailer test	no	gal./min. with	ft. drawdown after	hrs.
1	1	100	10	1
2	2	100	10	1
3	3	100	10	1
4	4	100	10	1
5	5	100	10	1
6	6	100	10	1
7	7	100	10	1
8	8	100	10	1
9	9	100	10	1
10	10	100	10	1
11	11	100	10	1
12	12	100	10	1
13	13	100	10	1
14	14	100	10	1
15	15	100	10	1
16	16	100	10	1
17	17	100	10	1
18	18	100	10	1
19	19	100	10	1
20	20	100	10	1
21	21	100	10	1
22	22	100	10	1
23	23	100	10	1
24	24	100	10	1
25	25	100	10	1
26	26	100	10	1
27	27	100	10	1
28	28	100	10	1
29	29	100	10	1
30	30	100	10	1
31	31	100	10	1
32	32	100	10	1
33	33	100	10	1
34	34	100	10	1
35	35	100	10	1
36	36	100	10	1
37	37	100	10	1
38	38	100	10	1
39	39	100	10	1
40	40	100	10	1
41	41	100	10	1
42	42	100	10	1
43	43	100	10	1
44	44	100	10	1
45	45	100	10	1
46	46	100	10	1
47	47	100	10	1
48	48	100	10	1
49	49	100	10	1
50	50	100	10	1
51	51	100	10	1
52	52	100	10	1
53	53	100	10	1
54	54	100	10	1
55	55	100	10	1
56	56	100	10	1
57	57	100	10	1
58	58	100	10	1
59	59	100	10	1
60	60	100	10	1
61	61	100	10	1
62	62	100	10	1
63	63	100	10	1
64	64	100	10	1
65	65	100	10	1
66	66	100	10	1
67	67	100	10	1
68	68	100	10	1
69	69	100	10	1
70	70	100	10	1
71	71	100	10	1
72	72	100	10	1
73	73	100	10	1
74	74	100	10	1
75	75	100	10	1
76	76	100	10	1
77	77	100	10	1
78	78	100	10	1
79	79	100	10	1
80	80	100	10	1
81	81	100	10	1
82	82	100	10	1
83	83	100	10	1
84	84	100	10	1
85	85	100	10	1
86	86	100	10	1

Artesian flow **no** g.p.m.

Temperature of water 54 Depth artesian flow encountered ft.

Drilling Machine Operator's Certification:

Well seal—Material used cement

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 20 in.

Diameter of well bore below seal 20 in.

Number of sacks of cement used in well seal 12 sacks

How was cement grout placed? from bottom up through tremie pipe

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John V. Datter Date Aug. 5, 1981
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1331

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Oetter Drilling & Irrigation Co.

Address P.O. Box 876 Crane, Ore. 97732

[Signed] John V. Petter

(Water Well Contractor)

Contractor's License No. 773 Date Aug. 5 1981