The original and first copy of this report are to be filed with the WATER WELL	L REPORTE LIVEU -) WS):	79F.	-12h
WATER RESOURCES DEPARTMENT, STATE OF	OREGON State Well No.		~.f._~	<u>.</u>
SALEM, OREGON 97310 (Please type within 30 days from the date	Stota Permit N	0		
of well completion. (Do not write ab	ove this line! ATER RESOURCES DEPT.		ž.	
* 4 1	SALEM. LECON			
(1) OWNER	(10) LOCATION OF WELL: G-8337			
Name Afterna Const	County Hamly Driller's well nu		W 4	tozalion
Address & D. Box 1/2	SE 14 NW 14 Section T. 24S		<u>7 E</u>	<u>W.M.</u>
Burns allgon	Bearing and distance from section or subdivision			80'5
(2) TYPE OF WORK (check):	Sontop of marter 1325' E from			
New Well (A Deepening Reconditioning Abandon	NW CONNER See 12			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 35 ft.			
Rotary Driven Domestic Industrial Municipal	Static level 38 ft. below land surface. Date \$9/22/			9/22/
Cable S. Jetted Dug Bored I Irrigation X Test Well Other	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded D	(12) WELL LOG: Diameter of well h	oelow cas	sing	2"
12 " Diam. from O ft. to 100 ft. Gage 250	Depth drilled 260 ft. Depth of compl	eted well	2	60 ft.
	Formation: Describe color, texture, grain size			
ft. Gage	and show thickness and nature of each stratu with at least one entry for each change of forma			
PERFORATIONS: Perforated?	position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	то	SWL
Size of perforations in, by in.	Soil	0	10	0
perforations from ft. to ft.	30il with arrvel	11	25	0
perforations from ft. to ft.	clay brown -	26	34	0
perforations from ft. to ft.	clay with gravel	35	55	25
perforations from to to	Claystone	56	80	25
(7) SCREENS: Well screen installed? Yes X No	clny, green	81	90	25
Manufacturer's Name	claystone	91	100	<u>25</u>
Type Model No	Rock, brown	101	110	25
Diam Slot size Set from ft. to ft.	cinystone	111	140	25
Diam. Slot size Set from ft. to ft.	clay, hard brown	141	150	<u> </u>
(8) WELL TESTS: Drawdown is amount water level is	SANdsTone	15-1	175	23
lowered below static level	Rock, Red	176	200	25
Was a pump test made? ☐ Yes 💆 No If yes, by whom?	gravel, medium	201	210	32
Yield: gal./min. with ft. drawdown after hrs.	chy, green hard	2//	220	27
" "	pumice, gray	22/	225	<u> </u>
n n n	MAY SOFT Brown	151	260	38 -
Bailer test gal./min. with () ft. drawdown after hrs.	erry, soft brown	797	200	<u> </u>
Artesian flow g.p.m.	· · · · · · · · · · · · · · · · · · ·	 		
perature of water Depth artesian flow encountered ft.	Work started 9/10 19 7 7Complet	ed G	7/22	19 77
	Date well drilling machine moved off of well	G	/23	19 77
(9) CONSTRUCTION: Well seal—Material used Cemen T	Drilling Machine Operator's Certification	:	/	
Well seal—Material used	This well was constructed under my	direc	t super	vision.
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	above	are true	e to my
Diameter of well bore to bottom of seal	•	D-4-		10
Diameter of well bore below sealin. Number of sacks of cement used in well seal sacks	[Signed](Drilling Machine Operator)	Date	787	, 19
How was cement grout placed?	Drilling Machine Operator's License No.			
now was cement grout placed?				
	Water Well Contractor's Certification:		5	
	This well was drilled under my jurisd	liction a	nd this i	report is
Was a drive shoe used? ☐ Yes XNo Plugs Size: location ft.	true to the best of my knowledge and be	nes	_ T~~	lando
Did any strata contain unusable water? Yes No	Name W. C. (Person, firm or corporation)		ype or pri	nt)
Type of water? depth of strata	Address P. P. Box 172 Bu	inio.	ally	2 977
	11.111 - 0 7	1. 1.		T).
Method of sealing strata off	[Signed] [] [Signed] (Water Well Cont	tractor)		Pres.
Was well gravel packed? ☐ Yes No Size of gravel:	Contractor's License No Date			19
avel placed fromft, toft	HEETS IF NECESSARY)			P*45656-119
(USE ADDITIONAL S	THEFT II. MECHONISTITI		۵	_ 10000 110