

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED STATE ENGINEER SALEM, OREGON OCT 17 1967

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

State Well No. 24/30-17 C

State Permit No.

830 Harney G-4491

(1) OWNER:

Name Adolph Kisle Address Burns, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [X] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

12" Diam. from 0 ft. to 120 ft. Gage 7.025

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used Torch Size of perforations 1/4 in. by 3 in. 105 perforations from 100 ft. to 120 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 9 ft. below land surface Date 10-14-67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? H. C. F. S. Yield: 1050 gal./min. with 61 ft. drawdown after 4 hrs. Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite Depth of seal 20 ft. Diameter of well bore to bottom of seal 16 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Harney Driller's well number NE 1/4 NW 1/4 Section 17 T.24 R. 30 W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 12 Depth drilled 324 ft. Depth of completed well 324 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Brown clay, Clay and gravel, Brown clay, Brown clay and gravel, Sandstone, Brown clay and gravel, Sand clay and gravel, Clay and Large gravel, Light brown clay & Med gr., Gray sandstone, Sand and med. gravel.

Work started 10-7-67 19 67 Completed 10-14 19 67 Date well drilling machine moved off of well 10-14 19 67

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Joe. Shannon Date 10-14-1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 116

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Western Drilling Co. (Person, firm or corporation) (Type or print)

Address P.O. Box 751 Burns, Oregon 97720

[Signed] J. W. McElh... (Water Well Contractor)

Contractor's License No. 426 Date 10-14-1967