

75 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion. STA

STATE ENGINEER
SALEM, OREGON^(P)

(Please type or print) **STATE ENGINEER**
SALEM, OREGON

State Well No.

State Permit No.

Name John Woods
Address Burns, Oregon 97720

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

Rotary	☐	Driven	☐	Domestic	☐	Industrial	☐	Municipal	☐
Cable	☒	Jetted	☐	Irrigation	☒	Test Well	☐	Other	☐
Dug	☐	Bored	☐						

CASING INSTALLED: Threaded ☐ Welded ☒
 12" Diam. from plus 1 ft. to 60 ft. Gage .250
 " Diam. from ft. to ft. Gage
 " Diam. from ft. to ft. Gage

Type of perforator used

Size of perforations	in. by	in.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield:	gal./min. with	ft. drawdown after	hrs.
	"	"	"
	"	"	"
Bailer test 150	gal./min. with	15 ft. drawdown after	1 hrs.
Artesian flow	g.p.m.		
Temperature of water	Depth artesian flow encountered ft.		

Well seal—Material used bentonite slurry

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 15 in.

Diameter of well bore below seal 12 in.

Number of sacks of cement used in well seal 0 sacks

Number of sacks of bentonite used in well seal 200# # ~~200~~

Brand name of bentonite bulk

Number of pounds of bentonite per 100 gallons
of water 1000 lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☒ Yes ☐ No

Type of water? sand depth of strata 10-15'

Method of sealing strata off casing

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

County Harney Driller's well number _____
SE ¼ NE ¼ Section 5 T. 24 S. R. 32 E. W.M.
 Bearing and distance from section or subdivision corner
100' W of E section line & 100' N of
center section line

Depth at which water was first found	ft.
Static level	25 ft. below land surface. Date 9-23-74
Artesian pressure	lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12"
Depth drilled 346 ft. Depth of completed well 346 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

[illegible]

Work started 9-6 1974 Completed * 2-23-75 1974
Date well drilling machine moved off of well 9-25 1974

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Forrest Blum Date 10-31, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No. 10

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Skinner & Sons
(Person, firm or corporation) (Type or print)

Address Crane, Ore. 97732
[Signed] Catherine Skinner
(Water Well Contractor)

Contractor's License No. 372 Date 10-31-, 1974