NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, ORECO within 30 days from the date of well completion.

JAN 15 1975 (Do not write above this line)

STATE ENGINEER

State Permit No.

(1) OWNER:	SALEM. OREGON	(10) LOCATION OF WELL:			
Name D. C. Dooley		County Harney Driller's well number			
Address 2485 W Main		TATUTE			
Littleton, Col	0 80120	NW 1/4 1/4 Section 16 T. 24S R. 321/F W.M. Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (ch	eck):	Bearing and distance from section or subdivision corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐					
If abandonment, describe material and procedure in Item 12.		(11) WATER INVELOR			
(3) TYPE OF WELL: (4) PROPOSED USE (check):		(11) WATER LEVEL: Completed well.			
Potary Driven Domestic Industrial Municipal Domestic Dome		Depth at which water was first found ft.			
		Static levelft. below land surface. Date			
Dag Dored D In	rigation X Test Well Other	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded □ Welded 5		(12) WELL LOG: #22ton of well halo			
14 " Diam. from0 ft. to372 ft. Gage14!!		Diameter of wen below casing			
" Diam. from ft. to ft. Gage		bepth drilled 3/2 - it. Depth of completed well 372 ft.			
" Diam. from ft. to ft. Gage		Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No.					
Type of perforator used Machi	ne-perforated	MATERIAL	From	то	SWL
Size of perforations 3/16	in. by 3 in.	Soil			
1920 perforations from	42 ft. to 82 ft.	Brown clay	-0-	70	
960 perforations from	172 ft. to 192 ft.	Green clay	70	32	
4800 perforations from	272 ft. to 372 ft.	Hard shale	32 37	37	
(7) CODERNO		Brown sandstone	39	39 42	
***************************************	reen installed? 🗌 Yes 🏻 No	Cinders, sand & gravel	42		
Manufacturer's Name Model No		Fine black sand	47	47	
		Blue clay	85	85	
	from ft. to ft.	Fine sand	172	172 182	
Blant, Slot size Set	from ft. to ft.	Green clay	182	262	
(8) WELL TESTS: Dra	awdown is amount water level is vered below static level	Brown & grey clay	262	282	
		Sand & gravel	282	302	
	No If yes, by whom? driller	Sandstone & clay layers	302	372	
	60 ft. drawdown after 8 hrs.				
<i>n</i>	15 15 15 7 1 1 1 1				
" "	" " " " " " " " " " " " " " " " " " "				
ler test gal./min. wi	th ft. drawdown after hrs.				
Artesian flow g.p.	.m.				
Temperature of water Depth a	rtesian flow encounteredft.				
		Work started Sept 4 19 74 Complete			19
(9) CONSTRUCTION:		Date well drilling machine moved off of well	Sept	10	19 7 5
Well seal—Material used	truction coment	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.		This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of seal24 in.		best knowledge and belief			
Diameter of well bore below seal24 in.		[Signed] J. Gulandon I	Date N.o.	r. 16	19 7/
Number of sacks of cement used in well seal		(Drilling Machine Operator)	م الله الله	• ···	, 20
Number of sacks of bentonite used in well seal sacks		Drilling Machine Operator's License No	7.3	8	
Brand name of bentonite		Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons		This well was drilled under my jurisdiction and this report is			
of waterlbs./100 gals. Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.		true to the best of my knowledge and belief.			
was a drive snoe used? [] Yes [] Yo Plugs Size: location ft. Did any strata contain unusable water? [] Yes [] No		Name John Truman Miller (Person, firm or corporation) (Type or print)			
		(Person, firm or corporation) (Type or print)			
Type of water? depth of strata Method of sealing strata off		Address P. O. Box 341 Hubbard, Oregon 97032			
weinod or sealing strata off		[Signed]			
Vas well gravel packed? Yes □ No Size of gravel: 1" minus		[Signed](Water Well Contractor)			
Fravel placed from20	ft. to	Contractor's License No277 Date			
					,