NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JAN 15 1975 STATE ENGINEER SALEM, OREGON

State Well No. 24S/32½E-16d
State Permit No. 957 Harn

(1) OWNER:
Name D. Dooley
Address 2485 W Main
~~Littleton, Colo. 80120~~

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
14" Diam. from 0 ft. to 246 ft. Gage ¼"
12" Diam. from 246 ft. to 346 ft. Gage ¼"
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Machine-perforated
Size of perforations 3/16 in. by 3 in.
480 perforations from 236 ft. to 246 ft.
4800 perforations from 246 ft. to 346 ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal 24 in.
Diameter of well bore below seal 24 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Harney Driller's well number
SE ¼ ¼ Section 16 T. 24S R. 32½E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found # 4 ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 346 ft. Depth of completed well 346 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Brown clay	0	36	
Black sand & sandstone	36	75	
Grey & green clay	75	205	
Sand	205	252	
Brown clay	252	290	
Coarse sand W.B.	290	298	
Grey clay	298	317	
Clay w/sand streaks	317	346	
pumice & volcanic rock			

Work started Sept 11 19 74 Completed 19
Date well drilling machine moved off of well Sept 13 19 74

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] G. C. Richardson Date Nov 16 19 74
(Drilling Machine Operator)
Drilling Machine Operator's License No. 738

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name John Truman Miller
(Person, firm or corporation) (Type or print)
Address P O Box 341 Hubbard, Oregon 97032
[Signed]
(Water Well Contractor)
Contractor's License No. 277 Date , 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119