NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

Co not write obe or print)

(Do not write obove this line)

State Well No. 24 SE-4d

State Permit No.

(10) LOCATION OF WELL: (1) OWNER: Driller's well number Name Mr. Walter Kleiner County Harney 5. W. 4 S. e 1/4 Section 9 T. 24/s R_ 33-e Address 1725- 89th. N.E. Bellvue, Wash. 98004 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): 300 due south of center of the see t-24-s/r-33-e. Abandon 🔲 New Well Deepening [Reconditioning [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 671 Rotary Driven 🗆 ft. below land surface. Date 6/30/78 Domestic | Industrial | Municipal | Static level 25 Jetted 🔲 Cable Irrigation Test Well Other lbs. per square inch. Date Dug Bored Artesian pressure CASING INSTALLED: Diameter of well below casing29 Threaded | Welded | (12) WELL LOG: 16" " Diam, from 0. ft. to 432 ft. Gage . 250 Depth drilled \$36 ft. Depth of completed well 432" Diam. from ft. to ft. Gage ... Formation: Describe color, texture, grain size and structure of materials; " Diam. from ft. to and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? *Yes | No. MATERIAL Type of perforator used factory louvered Size of perforations 1/8 in. by $2\frac{1}{5}$ in. t<u>op s</u>oil 4 sand (hard) 12 8.640 perforations from 240 ft. to 432 62 tan&blue clay perforations from ft. to 74 67 black sandstone perforations from ft. to ... 282 olack/gray/green clays 74 (7) SCREENS: gray sandstone 282 289 Well screen installed?

Yes *No 289 294 Manufacturer's Name med. sand& gravel 294 303 green sandstone&pumis Diam. Slot size Set from ft. to ft. to 303 311 <u>gray sandstone</u> Diam. Slot size Set from ft. to ft. 311 sandstone & pumis green claystone&pumis (8) WELL TESTS: Drawdown is amount water level is lowered below static level
well to be tested at later date.
Was a pump test made? | Yes | No II yes, by whom? 346 370 grav sandstone & pumis black sandstone&clavstone370 413 413 420 green claystone Yield: gal./min. with ft. drawdown after hrs. 420 436 green sandstone&pumis blue&green clay gal./min. with ft. drawdown after Bailer test Artesian flow g.p.m. 1978 Completed 6/30/78 19 perature of water 63 Depth artesian flow encountered ft. Work started 29/ Date well drilling machine moved off of well 6/30/ 1978 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used cement grout This well was constructed under my direct supervision.

Materials used and information reported above are true to my best knowledge and belief.

[Signed]

(Drilling Machine Operator)

Date 19 Diameter of well bore below seal29! in. Drilling Machine Operator's License No. ..., Number of sacks of bentonite used in well seal sacks Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief.

Name WESTER IN WIGHER UP Was a drive shoe used?

Yes No Plugs Size: location ft. (Person, firm or corposation) Did any strata contain unusable water?

Yes
No Type of water? depth of strata Method of sealing strata off [Signed] Was well gravel packed? Tyes \(\) No Size of gravel: 3/8.... Contractor's License No. (2) Gravel placed from 18 ft. to 135 ft.