The original and fire opin to this report are filed with the MAR 13 1369 WATER WELL REPORT STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) within 30 days from the date it is to be considered to the completion of well completions A LEAS OF THE COMPLETE CONTROL OF THE CO

HOOD State Well No. 2N/B-6 da State Permit No.

(1) OWNER:	(11) LOCATION OF WELL:	1/5	GA
Name CITY OF CASCADE LOCKS Address CASCADE LOCKS ORE.	County HOOD KIVER Driller's well nu		77_
Address CASCADE LOCKS ORE	NE 14 5E 14 Section 6 T. 21		<u>W.M.</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	1 corner	
New Well X Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Rotary Driven Domestic Industrial Municipal	(12) WELL LOG: Diameter of well b		/
Cable	Depth drilled 164 ft. Depth of comple	eted well / O	94 ft.
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratus		
CASING INSTALLED: Threaded Welded Welded	with at least one entry for each change of form	ation. Report ea	ch change
S Diam from tt. to 109 ft. Gage : 377	in position of Static Water Level as drilling pro	ceeds. Note drill	ing rates.
" Diam. from	MATERIAL	From To	SWL
from ft. to ft. Gage	SANDY SILT	0 2	
PERFORATIONS: Perforated? (Yes No.	GRANEL AND BOULDERS	2 7	
Type of perforator used STAR	SAND GRAVE, BOULDERS,		
Size of perforations 3/8 in. by //4 in.	AND SOME CLAY	7 26	┼──
600 perforations from 35 ft. to 100 ft.	LOOSE SAND AND GRAVEL	40 109	
perforations from ft. to ft.	ZOUSE STAND HAND GRAVE	70 70	'
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name		<u> </u>	
Type Model No			
Diam. Slot size Set from the ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WATER LEVEL: Completed well.			
· · · · · · · · · · · · · · · · · · ·			
			——
sian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? MYes □ No If yes, by whom? STRASSER			
"eld: 3/10 gal./min. with / ft. drawdown after 8 hrs.	Work started JAN 7 1969 Complete	ad $FE/3$	6 19 6 9
, , , , , , , , , , , , , , , , , , ,	Date well drilling machine moved off of well	FE13	7 19 6
N N N	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di		
	rials used and information reported above knowledge and belief.	e are true to	my best
Artesian flow g.p.m. Date	Na 1) remain	Born MAR	12,69
Temperature of water 43 Was a chemical analysis made? Yes No	[Signed] (Drilling Martine Operator)	Date	::., 19 <i>!</i>
(10) CONSTRUCTION: JAND AND	Drilling Machine Operator's License No	57	
Well seal-Material used CEMENT GROUT			
Depth of seal ft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdi true to the best of my knowledge and belie	ction and this	report is
Were any loose strata cemented off? Yes No Depth	NAME RISTRASSEE D	RILLING	6
Was a drive shoe used? X Yes □ No	(Person, firm or corporation)	(Type or print	
Did any strata contain unusable water? Yes No	Address 8110 SE SUNET LANCE	· HORTLA	NO ORI
Type of water? depth of strata	PO-1-9 11	7724	
Method of sealing strata off	[Signed]	ser	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contract	.tor)	10
Gravel placed from # 10 ft	Contractor's License No. / Date /	MAR 12	1967