R-HOOD 50299

' STATE OF OREGON

WATER SUPPLY WELL REPORT OCT 2 9 2001

(as required by ORS 537.765)
Instructions for completing this report are on the last page of this form

A A FRA. ODEON

(START CARD)# 134419

| (1) OWNER:  |  | SAMelviyumbe                        | (9) LOCATION OF W     |   |                                | onaituda                                |                     |        |
|---|--|-------------------------------------|-----------------------|---|--------------------------------|---|---------------------|--------|
|   |  | c. (George Wertge                   | en)                   |   | River Lati<br>For S. Range 101 | *************************************** | ongitude<br>W. of W |        |
| Address 2875 F  |  | State OB                            | Zip <b>97031</b>      | Section 1 SW 1/4 SW 1/4   |                                |   |                     |        |
| City Hood   |  | Otate OK                            | Zip 3/03 [            | Tax lot 1900 Lot  |                                | Subdivi                                 |                     |        |
| (2) TYPE OF \   |  |                                     |                       | Street Address of Well (o                                       | or nearest address) 47         | 00 Norman I                             | Rd. Ho              | od     |
| X New Well  | Deepening Al   | teration (repair/recondit           | ion) Abandonment      |   | I EVEL.                        |   |                     |        |
| (3) DRILL ME  | THOD:  |                                     |                       | (10) STATIC WATER 532 ft. below                                 | LEVEL:<br>v land surface.      | Da                                      | te 08/3             | 1/2001 |
| X Rotary Air  | Rotary Mud   | Cable                               | Auger                 | Artesian pressure   |                                |   |                     |        |
| Other   |  |                                     |                       | (11) WATER BEARIN   | IG ZONES:                      |   |                     |        |
| (4) PROPOSE   | D USE:   |                                     |                       | Depth at which water wa   |                                |   |                     |        |
| Domestic  | ☐ Community  | Industrial                          |                       | <u> </u>  |                                |   |                     |        |
| Thermal Injection Livestock Other   |  | Other                               | From To Esti          |   |                                | imated Flow Rate                        |                     |        |
| (5) BORE HOLE CONSTRUCTION:   |  |                                     |                       | 680 722   |                                |   | 100                 |        |
| Special Constructi  | ion approval Yes   | X No Depth of Co                    | ompleted Well 722 ft. |   |                                |   |                     |        |
| •   | Yes X No Type  |                                     | mount                 |   |                                |   |                     |        |
| HOLE Diameter From  | To Mat   | <b>SEAL</b><br>terial From T        | o 🚅 sacks or pounds   | (12) WELL LOG:  |                                |   |                     |        |
| 16" 0   | 25 Cement  |                                     | 5 11 Bags             |   | Ground elev                    | ation                                   |                     |        |
| 12" 25  |  | TWEATCH AT                          |                       | From  | То                             | SWL                                     |                     |        |
| 10" 340   | 10" 340 722  |                                     |                       | Clay Stone Hard Brown Sandstone Fine Brown                      |                                | 0                                       | 33                  |        |
|   |  |                                     |                       | Clay Stone & Sands  |                                | 33<br>47                                | 47<br>95            |        |
|   | Sandstone Coarse Brown   |                                     | 95                    | 120   |                                |   |                     |        |
| How was seal placed: Method A B XC D E  Other  Gravel Med. Brown  Clay Soft Brown |  |                                     |                       | 120   | 135                            |   |                     |        |
| Backfill placed from  | m ft. to   | ft. Material                        |                       | Clay Soft Brown Rock Broken Brown                               | <u> </u>                       | 135<br>145                              | 145<br>176          |        |
| Gravel placed from  |  | ft. Size of grav                    | el                    | Gravel Med. Multi Co  |                                | 176                                     | 245                 |        |
| (6) CASING/L  | INER:  |                                     |                       | Rock Soft Brown   |                                | 245                                     | 280                 |        |
| Diamete   |  | Gauge   Steel Plas                  | tic Welded Threaded   | Rock Soft Fract. Bla<br>Rock Broken Black                       | ck                             | 280<br>320                              | 320<br>354          |        |
| Casing: 12"   | +1 24  | .250 X                              | <b>X</b>              | Basalt Hard Fract. B  | lack                           | 354                                     | 367                 |        |
| 10"   | +1.5 323.5   | .250 X                              | X                     | Basalt Hard Black   |                                | 367                                     | 405                 |        |
|   |  |                                     |                       | Basalt Soft Fact. Bla<br>Basalt Hard Fract. G                   |                                | 405<br>410                              | 410                 |        |
| Liner:  |  |                                     |                       | Basalt Hard Gray  | пау                            | 445                                     | 445<br>455          |        |
|   |  |                                     |                       | Sandstone Coarse Brown  |                                |   | 630                 |        |
| Final location of sl  | hoe(s) <u>323.5</u>  |                                     |                       | Rock Soft Black   | /F-D                           | 630                                     | 680                 |        |
| (7) PERFORA   | TIONS/SCREEN   | NS:                                 |                       | Rock Broken Black   | VED                            | 680                                     | 722                 | 532    |
| Perforation   |  |                                     |                       |   |                                |   |                     |        |
| Screens   | Туре   | Materi                              |                       | SEP 0.7   | 2001                           |   |                     |        |
| From To   | Slot<br>size Number  | Tele/pipe<br>Diameter size          | Casing Liner          | WATER RESOURCE SALEM, ORE                                       | CES DEPT.                      |   |                     |        |
|   |  |                                     |                       |   |                                | eted 08/31/20                           |                     | i      |
|   |  |                                     |                       | (unbonded) Water Well   |                                |   | <u> </u>            |        |
|   |  |                                     |                       | I certify that the work I per                                   |                                |   | abando              | nment  |
| (8) WELL TES  | STS: Minimum to  | esting time is 1 h                  | our                   | of this well is in compliance                                   |                                |   |                     |        |
| Pump  | Bailer   | X Air                               | Flowing Artesian      | Materials used and informat belief.                             | ion reported above are         | true to my best ki                      | nowledge            | e and  |
|   |  | Lacounties and a                    |                       |   |                                | WWC Numb                                | er                  |        |
| Yield gal/min   | Drawdown   | Drill stem at                       | Time                  | Signed  |                                | Date                                    |                     |        |
| 100   |  | 720                                 | 1 hr.                 |   |                                |   | <del></del>         | ···    |
|   |  |                                     |                       | (bonded) Water Well Co  |                                |   | <b>-</b>            |        |
|   |  |                                     |                       | I accept responsibility for to<br>performed on this well during |                                |   |                     |        |
| Temperature of W  |  | Depth Artesian Flow fou             | nd                    | performed during this time i                                    | s in compliance with Or        | egon water supp                         | ly well             |        |
| •   | sis done? Yes  | By whom                             | Taglima               | construction standards. The                                     | report is true to the bo       |   |                     |        |
| Did any strata con<br>Salty Mud   | tain water not suitable<br>dy           Odor                 C | e for intended use?<br>olored Other | Too little            | Signed A  | Als Cant                       | WWC Numb                                | er <u>790</u>       |        |
| Depth of strata:  |  |                                     |                       | Charles Austin  |                                |   | 44UU                |        |
|   |  |                                     |                       |   |                                | <del></del>                             |                     |        |