NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be WATER WEI	L REPRECEIVED			
of this report are to be filed with the	OREGON SEP6 1974 State Well No	265	2/41	1-17
STATE ENGINEER, SALEM, OREGON 97310 STATE OF	OREGON SEPO 1314 State Well No		2	U /
within 30 days from the date	STATE ENGINEER State Permit	No		
of well completion. (Do not write a)	SALEM, OREGON	1	73/	7/
(1) OWNER		<u> </u>	<u>/U</u>	71
(1) OWNER:	(10) LOCATION OF WELL:			
Name (1) (AEO)()	County Driller's well	ıumber		
Address 100 Kolif Livik Huy	TACKSON 1/4 Section 12 T. 36	5 R. 46	al	W.M.
COMMENTS PAGE , DE 4	Bearing and distance from section or subdivi			-
(2) TYPE OF WORK (check):				
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Don'th at which we take a 19			
Rotary D Driven D	Depth at which water was first found ft.			
Cable	Static level 20 ft. below land surface. Date 8/9/>9			
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well	below cas	ing 6	, "
6 "Diam from 0 ft. to 64/2 ft. Gage . 250	Depth drilled 80 ft. Depth of comp	oleted well	80) _{ft.}
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size	and struc	ture of	materials:
ft. Gage	and show thickness and nature of each strat	um and ac	quifer pe	enetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of form position of Static Water Level and indicate pri			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.		0	11	
perforations from ft. to ft.	CLAY, BEN, GRAVEL, SM			
perforations from ft. to ft.	CLAY, BEN	11	33	
perforations from ft. to ft.				
	SEACTURED BASALT (SOFT)	33	57	1
(7) SCREENS: Well screen installed? Yes Wo				
Manufacturer's Name	FRACTURED BASALT (HARO)	57	80	20
Type Model No				· .
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	Aguifer	69	78	223/1
(8) WELL TESTS: Drawdown is amount water level is				<i>''</i>
lowered below static level		1		
Was a pump test made? Wes \(\subseteq \text{No If yes, by whom? ORILLER} \)				ļ
Yield: 22 gal./min. with 3 ft. drawdown after hrs.	***			
" " "		+		
n n		+	·	<u> </u>
Bailer test gal./min. with ft. drawdown after hrs.				<u> </u>
Artesian flow g.p.m.		1		
		- 		
nperature of water / Depth artesian flow encountered ft.	Work started \$\sqrt{S} 19 Y Comple	ted 8	?	19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8/9	<u>}</u>	19 7 9
Well seal—Material used CE MENT	Drilling Machine Operator's Certification	.: /		
Well sealed from land surface to 3.5 ft.	This well was constructed under my	direct	super	rvision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above a	ire true	e to my
Diameter of well bore below seal in.	[Signed] O. L. Oreisher	Data S	151	10.74
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	Date9	f 	, 19
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	8/	0	
Brand name of bentonite		····································		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			y.
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? ✓ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief			
Did any strata contain unusable water? 🗌 Yes 🖫 No	Name (Ferson, firm or corner tion)		pe or pri	int)
Type of water? depth of strata	Address 849/Weblow	KW		
Method of sealing strata off	Who tola -			
Was well gravel packed? ☐ Yes TNO Size of gravel:	[Signed] Water Well Conf	ractor)		*
Gravel placed from ft. to ft.		9-1	•	Z
11. IV It,	Contractor's License No. 2	-f		, 18//