STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

JUN 8 1984

PLEASE TYPE or PRINT'IN INK
SALEM. OREGON

2	e>/ <	HW	-/5	
	7		······································	١
	/ '		ce	

	SALEM, OREGON	(for official use	only)
(1) OWNER:	(10) LOCATION OF WELL by lega	l descriptio	n•
Name City of Rogue River		of Section 15	
Address P.O. Box Q	Township 36 P	W section	oi
City Rogue River State Ore. 97537	(Township is North or South)	(Range is East or Wes	t) , vv ivi
(2) TYPE OF WORK (check):	Tax Lot 600 Lot Block Subdivision		
T-X	MAILING ADDRESS OF WELL (or nearest address)		A
New Well			
	(11) WATER FRIEN		
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Air XX Driven	(11) WATER LEVEL of COMPLET	ED WELL:	
Thermal		72	ft
Rotary Mud Dug Irrigation Withdrawal Reinjection		land surface. Date	<u>5/30/8</u>
Cable	Artesian pressure lbs. per	square inch. Date	
(5) CASING INSTALLED: Steel XX Plastic	(12) WELL LOG: Diameter of well below	v casing	3"
Thursday [NY 13 1 VV		f completed well	<u>300 ft</u>
8 "Diam. from +1½ ft. to 39 ft. Gauge .250	Formation: Describe color, texture, grain size and structure and nature of each stratum and aquifer penetrated, with at l	of materials; and sh	ow thickness
	formation. Report each change in position of Static Wat	er Level and indic	ate principa
LINER INSTALLED: Steel Plastic	water-bearing strata.		
Threaded Welded	MATERIAL	From To_	SWL
ft. Gauge	Boulders + Clay med Brown		
(6) PERFORATIONS: Perforated? Yes X No	Gravel ## Clay Med Brown	18 31	
Size of perforations in. by in.	Claystone Brown	31 51	
perforations from ft. to ft.	Claystone Fractured Brown	51 80	22
perforations from	Claystone Fractured Gray	80 102	22
perforations from	Basalt Gray Basalt Fractured Brown	102 171	00
	Basalt Gray	171 173	22
(7) SCREENS: Well screen installed? Yes No	Basalt Black	173 243	
Manufacturer's Name	DABAITO DIACK	243 300	
TypeModel No.			ļ
Diam. Slot Size Set from ft. to ft. Diam. Slot Size Set from ft. to ft.			
			1
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			-
Was a pump test made? ☐ Yes ☒ No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.			
" " "			
Air test 100 # gal./min. with drill stem at 300 ft. 3 hrs.			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water 49 Depth artesian flow encounteredft.			
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\frac{\frac{1}{2}}{2} \)	Date work started 5/29/84/complete	_d 5/30/	84
(9) CONSTRUCTION: Special standards: Yes □ No ♠X Well seal—Material usedCement	Date well drilling machine moved off of well	5/30	1984
Well sealed from land surface to	(unbonded) Water Well Constructor Certifica	tion (if applica	ble):
Diameter of well bore to bottom of seal12_5/8 in.	This well was constructed under my direct supe	ervision. Material	ls used and
Diameter of well bore below seal	information reported above are true to my best kno	wledge and belie	f.
Amount of sealing material	[Signed]	Date	19
How was cement grout placed? Pressure Pumped			., 10
	(bonded) Water Well Constructor Certificatio		
7.55	Bond 42s 39337BCA Issued by: Etna Li	ty Company Name)	
Was pump installed? NO Type HP Depth ft.	On behalf of Gribble Well Drilling		
Was a drive shoe used? 🛣 Yes 🛘 No Plugs Size: location ft.	(type or print name of Wat	er Well Constructor)	
Did any strata contain unusable water? 🔲 Yes 💢 No	This well was drilled under my jurisdiction an	d this report is t	rue to the
Type of Water? depth of strata	best of my knowledge and belief:	•	
Method of sealing strata off	(Signed) Milkowsh		
Was well gravel packed? Yes No Size of gravel:	(Water Well Constructor	r)	***************************************
Gravel placed from ft. to ft.	(Dated)	4	