NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)
(Do not write above this line)

State Well No. 365	Hw-	154
	1	

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name City of Rogue River	County Jackson Driller's well number 791		
Address 133 Broadway	SE 14 SW 14 Section 15 T. 36 R. 4W W.M.		
Rogue River, OR 97537	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Tax Lot 600		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 45 ft.		
Rotary 🛚 Diven 🗍 Domestic 🗎 Industrial 🗎 Municipal 📆	Static level 15 ft. below land surface. Date 1/23/80		
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded □ Welded Kk 8 " Diam. from 0 ft. to 32 ft. Gage 250 " Diam. from ft. to 5 ft. Gage 5	(12) WELL LOG: Diameter of well below casing 8 Depth drilled 100 ft. Depth of completed well 100 ft.		
PERFORATIONS: Perforated? Yes XX No.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Boulders & Clay, brown 0 15		
perforations from ft. to ft.	Clay, brown & Gravel 15 27		
perforations fromft. toft.	Shale, brown 27 45		
perforations from ft. to ft.	Shale, fractured 45 80		
(7) SCREENS: Well screen installed? ☐ Yes 本No	Shale, grey fractured hard 80 100 15		
Manufacturer's Name			
Type Model No			
Diam Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED		
a pump test made? Yes XXNo If yes, by whom?			
gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT		
" " "	SALEM. OPEGON		
Air " "	Administration of the Carlotte		
gal./min. with 75 ft. drawdown after 1 hrs.			
esian flow g.p.m.			
perature of water 48 Depth artesian flow encounteredft.	Work started 1/22 19 80 Completed 1/23 19 80		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1/23 19 80		
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:		
Well sealed from land surface toft. Diameter of well bore to bottom of seal 12 5/8 in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge, and belief		
Diameter of well bore below seal8 in. Number of sacks of cement used in well seal 12 sacks	[Signed] Jaly Julian Machine Operator) 1/24 , 19 80		
How was cement grout placed?	Drilling Machine Operator's License No. 1167		
Grode point and Grop pape.	Water Well Contractor's Certification:		
A History Control of the Control of	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ⊠XYes □ No Plugs Size: location ft. Did any strata contain unusable water? □ YesX⊠ No	Name McClanahan Well Drilling		
Type of water? depth of strata	(Person, firm or corporation) (Type or print) Address 141 NE Beagon Drive Grants Pass, OR		
Method of sealing strata off	[Signed] Kan Milanahan		
Was well gravel packed? ☐ Yes XX No Size of gravel:	(Water Well Contractor)		
Gravel placed fromft. to ft.	Contractor's License No. 727 Date January 24, 1980		