NOTICE TO WATER WELL CONTRACTOR

water resources department, Salem, Oregon 97310 within 30 days from the date of well completion.

water well report? 01979

MEGENEU

STATE OF OREGON RESOURCES DEPT

(Please type or print) LEM. OREGON State Permit No.

(Do not write above this line)

	!
(1) OWNER:	(10) LOCATION OF WELL:
Name PRESTON FULBRIGHT	County ACKSON Driller's well number
Address P. O. Box 1/0/	S.E. 15, E 1/4 Section 21 DT34 S R. 1 W. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
	TAX LOT 00403
New Well Deepening Reconditioning Abandon	20055 HWY 62
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 20 ft. below land surface. Date \\ -28-7
□ Bored □ Irrigation □ Test Well □ Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOC.
6 "Diam from O ft to 40 ft Gage 250	(12) WELL LOG: Diameter of well below casing
H Diam. from O ft. to 183 ft. Gage 160 P.S.T.	Depth drilled 1855 ft. Depth of completed well 1855 ft.
ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? **Z Ves \(\text{I} \) No	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
C restorated, M res [] Ho.	
V/a	MATERIAL From To SWL
Size of perforations 78 in. by 6 in. 192 perforations from 103 ft. to 183 ft.	Soil Drown O I
perforations from ft. to ft.	Roulders & Sant Brown 1 17 Claystone - Blue 17 37
perforations from ft. to ft.	Sandstone-Blue 37 64
	Clar Stone-Blue 64 79
(7) SCREENS: Well screen installed? Yes No	Syndstone-Blue 79 107
Manufacturer's Name	Sand stone - Block / Gray 107 110
TypeModel No DiamSlot size Set from ft. to ft.	Sand Stone- Black / Rel 10 132
Diam. Slot size Set from ft. to ft.	Sandstone-Blue (Red 140 159
	Sandstone-Buc 159 183 20
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
a pump test made? The Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
n n	
" " "	
Soiler test 100 gal./min. with 63ft. drawdown after hrs.	
ian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 11-27 1979 Completed 11-28 1979
(9) CONSTRUCTION: \\	Date well drilling machine moved off of well 11-28 1979
Well seal-Material used Fortland Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to 3.8 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and ballef.
Diameter of well bore below seal	[Signed] Date 11-28, 1919
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 1229
Iremic Pipe	Water Well Contractor's Certification:
三 三 三	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? X Yes \(\subseteq No_Plugs Size: location	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name (Person, firm or comporation) (Type or brint)
Type of water? depth of strata	Address & BAGUE POWT NEE
Method of sealing strata off	Do College
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 667 Date 11-28

(USE ADDITIONAL SHEETS IF NECESSARY)